
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

None



No record of subsequent monumentation found in Union County survey records

DESCRIPTION OF CORNER EVIDENCE FOUND:

None

See Union County Survey Number 034-1996.

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED

TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the position determined by survey, I set a 5/8"x30" rebar with $1\frac{1}{2}$ " aluminum cap marked as shown, 26 inches in the ground, with ring of stone, from which;

NEW BEARING TREES:

A 12" Diameter Ponderosa Pine bears N59°E, 17.63 feet, marked NN 1/64 S17 BT. A 11" Diameter Ponderosa Pine bears N66°W, 34.51 feet, marked NN 1/64 S18 BT.


I hereby certify that the corner was monumented on August 12, 1996. Witness: Jeff Madsen, Mark Durbin

> REGISTERED **PROFESSIONAL** LAND SURVEYOR

ORÉGON

JEFFERY P. PETERSEN 2625

Ronewal Date: December, 31 1996



UNION COUNTY **SURVEYOR**

Date Received 8-15-96

Date Filed 8-15-96

Filed By R. R. KINSIN, DEARY

File Number 091-1996R

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 17° East declination, the distances are to 50d spike driven in the right side of the root crown of the bearing trees. I attached a brass washer marked OPLS 2625 to the BT Blaze.