


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

N-5

History of original corner establishment:



CORNER SET BY KIMBRELL IN OCTOBER 1891

A POST 4' LONG 4" SQUARE 24" IN THE GROUND

- 22" PINE S61E 45LKS. MKD. TIN R38E S20 BT
- 9" FIR N63E 85LKS. MKD. TIN R38E S17 BT
- 4" FIR N19W 42LKS. MKD. TIN R38E S18 BT
- 14" FIR S29W 100LKS. MKD. TIN R38E S 19 BT

Description of corner evidence found:

RED PAINTED STAKE IN SMALL MOUND OF STONES

36" PINE S61E 45LKS. GROWING TREE, SCRIBING HEALED OVER

Description of monument and accessories established to perpetuate the original location of this corner:


SET 2"x30" IRON PIPE WITH BRASS-CAP MARKED:

TIN R38E
 S18 S17
 S19 S20
 1978
 RLS 346

- 16" FIR S40W 54.2' MKD. TIN R38E S19 BT
- 8" FIR N37E 21.7' MKD. TIN R38E S17 BT
- 12" FIR N62W 17.3' MKD. TIN R38E S19 BT

ALL TREES HAVE A RED PAINTED STRIPE AND BT SIGNS. THE NEW TREES HAVE A BRASS WASHER STAMPED RLS 346 NAILED TO THE LOWER BLAZE. THERE IS A 6' STEEL FENCE POST ON LINE APX. 5' FROM THE CORNER.

THERE IS A BLAZED LINE RUNNING NORTH FROM THIS CORNER,



Office of..... COUNTY SURVEYOR..... County of..... UNION.....
 OREGON

State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....

..... by
 (COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	_____
By	_____
File No.	70-84R