
HISTORY OF ORIGINAL CORNER ESTABLISHMENT: Corner originally established by Joseph G. Gray on a joint venture with O'Dell under GLO contract Number 120, dated May 27, 1867. Surveyor General record states:

Set 1/4 sec. cor. post, deposited marked stone and raised stone mound.



DIAGRAM

No record of subsequent monumentation found in Union County survey records. DESCRIPTION OF CORNER EVIDENCE FOUND: Found stone 17x10x6 inches marked 1/4, loose in fence jack. The stone has been moved, I placed the monument at the intersection of fence lines, which run out in all four directions. I accept this as best available evidence of the location of the original corner,


See Map of Survey No. 034-1994 DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: In the position determined as stated above, I set a  $2\frac{1}{2}$ " x 30" aluminum pipe with aluminum cap marked as shown, 10 inches in the ground, from which;

NEW BEARING TREES:

A 10 inch diameter Ponderosa Pine bears N 79° E, 15.83 feet marked X BT A 11 inch diameter Ponderosa Pine bears S 48° E, 32.53 feet marked 1/4 S23 BT A 14 inch diameter Ponderosa Pine bears N 81° W, 61.94 feet marked 1/4 S22 BT A 10 inch diameter Ponderosa Pine bears N 17° W, 32.07 feet marked 1/4 X BT

Buried stone west and along side pipe.

Raised a mound of stone around monument, 4 foot base to top of cap. Painted a 6" red band around all BTs and attached Bearing Tree signs.



UNION COUNTY SURVEYOR Date Received 812 Date Filed File No. 033

I hereby certify that the above corner point was perpetuated as hereon described on June 21, 1994. Witnesses: Travis Foster and Pete Crabtree.

ORSIG ...11 JULY 10, 1964 OUANE I. GRIFFITH 644

I used a steel tape and magnetic compass in the establishment of new accessories. I used 20° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

P-17