

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

(T1NR39E)

L-251


History of original corner establishment:

Survey was performed by Timothy W. Davenport, Deputy Surveyor, under Contract No. 102 dated July 20, 1863. He set a wood post for the 1/4 corn. common to Sections 13 & 18 T 1 N R 38 & 39 E.

The bearing trees were:

A pine 28" dia. bears N 68 E, 148 lks. dist. scribed 1/4 S BT.

A pine 8" dia. bears S 50 E, 183 lks. dist. scribed 1/4 S BT.



Description of corner evidence found:

I found a pine alive and 39" dia. with a face exposed with 1/4 S BT on the face. Also I found a pine stump approx. 16" dia. and evidence of it being the second bearing tree as it fit the GLO call distance and bearing.

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a stamped 2 1/2" brass cap on a 30" galv. iron pipe at the 1/4 corner location by intersecting the GLO bearings & distances from the two found trees, I then placed a large mound of stone about the monument, it is located approx. N 45 E, 0.75 feet from a 14" pine.

I then set new bearing trees as follows:

A pine 11" dia. bears N 35 E, 38.0 feet and scribed 1/4 S S 18 BT.

A pine 10" dia. bears N 36 W, 79.7 feet and scribed 1/4 S S 13 BT.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton
3-20-78

OREGON
JULY 10, 1964
JAMES H. HAMBLETON
645

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office

for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	_____
By	_____
File No.	91-84 R