


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. E-03

History of original corner establishment:



Original corner established in 1898 by Alonzo Gesner under contract #683.
 He set a Tamarack Post 4'x4"x4", 24" in ground.
 From which:
 An 18" White Fir bears N0°30'E, 115 lks.
 A 16" Tamarack bears S74°30'E, 50 lks.

Description of corner evidence found:

No corner monument found.
 No bearing trees found.

Description of monument and accessories established to perpetuate the original location of this corner:

By single proportioning, I set 2½"x30" aluminum capped aluminum pipe rising 8" above ground in a mound of stones. Set a steel fence post 3 ft. north of corner.	Cap is stamped: T1S R41E $\frac{1}{4} \frac{S6}{S7}$ RLS1848 1986
--	---

New BT's:


A 16" Doug Fir bears N50½°E, 60.6 ft., blazed&scribed: ¼S6BT
 A 12" Doug Fir bears S55½°E, 56.5 ft., blazed&scribed: ¼S7BT

Painted blazes and attached signs as required in Specifications for Cadastral Surveys, USFS Region 6, March, 1982. A ¾" brass disk stamped "RLS1848" is nailed to lower end of blazes.

To find corner follow Rd. 6200610 Southeasterly ¼ mile from 6200600. Corner is 300 ft. west up the hill on steep easterly slope.

Compass Declination: 19½°E
 Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on Oct. 20, 1986.



UNION COUNTY SURVEYOR	
Date Received	<u>12-1-86</u>
Date Filed	<u>12-2-86</u>
By	<u>G. LANGLITZ, DEPUTY</u>
File No.	<u>284-86 R</u>

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)