

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


Index File No. E-05

History of original corner establishment:

Original corner established in 1898 by A. Gesner under contract #683. He set a basalt stone, 16"x14"x7", 12" in ground.

From which:

- A 24" Tamarack bears N44½°E, 39 lks.
- A 20" Fir bears S34½°E, 8 lks.
- A 10" Fir bears S5½°W, 45 lks.
- An 8" Fir bears N31°W, 25 lks.



Description of corner evidence found:

Found original stone with notches.

Bearing trees found:

- A 21" Fir bears S15½°W, 29.7 ft., blaze healed.
- A 29" Fir bears N21½°W, 16.5 ft., blaze healed.
- A dead&down tamarack in NE quadrant, badly decayed no marks.
- A 25½" Fir stump, 7 ft. tall, bears S30½°E, 5.3 ft., blaze healed.

Description of monument and accessories established to perpetuate the original location of this corner:

From evidence, set 2½"x30" aluminum capped aluminum pipe rising 6" above ground. Deposited original stone in hole along north side of cap. Set steel fence post 3 ft. north of corner.

Cap is stamped:

T1S R41E
<u>S6 S5</u>
S7 S8
RLS 1848
1986

New BT's:

- A 7" Fir bears N14°E, 22.6 ft., blazed&scribed: T1SR41ES5BT
- A 6½" Fir bears S59½°E, 33.8 ft., blazed&scribed: T1SR41ES8BT

Painted blazes and attached signs as required in Specifications for Cadastral Surveys, USFS Region 6, March, 1982. A ¾" brass disk stamped "LS1848" nailed to lower end of blazes. From intersection of 6200 with 6200530 go S30°E 350 ft. to corner.

Compass Declination: 19½°E  
Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on July 13, 1986.



<b>UNION COUNTY SURVEYOR</b>
Date Received <u>11-21-86</u>
Date Filed <u>11-26-86</u>
By <u>G. LANGRISH, DEPUTY</u>
File No. <u>273-86 R</u>

Office of..... County of.....  
 State of....., I hereby certify that the within instrument was filed in this office  
 for record on the..... day of....., 19.....  
 ..... by .....  
 (COUNTY OFFICIAL) (DEPUTY)