

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


N-13

History of original corner establishment:

Original survey by contract #382 dated March 28, 1881

Notes read.;

Set post to Sec. 15,16,21,22 from which;  
Apine 26" in diam bears N27°E 42 lks. dist;  
Apine 34" in diam bears N43°W 101 lks dist;  
Apine 42" in diam bears S85°W 43lks dist.;  
A pine 24" in diam bears S43°#24 lks dist.;



Description of corner evidence found:

A down log with scribe found at S85°W 43 lks dist.;  
A stump with scribe found at N27°E at 42 lks dist.;  
A down log found and N43°W 101 lks dist with scribe.;


Description of monument and accessories established to perpetuate the original location of this corner

At the position of the corner I set a 2" pipe 30" long with a brass cap and at a depth of approx. 20".

From the Corner the following bearing trees were established.;

A ponderosa pine 9" in diam bears N21°30"W a dist. of 65 ft. scribed T2N R40E S16BT;  
A ponderosa pine 14" in diam bears S76°W a dist of 57.3 ft. scribed T2N R40E S21BT;  
A ponderosa pine 12" IN DIAM BEARS N13°25"E a dist of 69.5ft. scribed T2N,R40E,S15BT;  
A ponderosa pine 15" in diam bears S67°E a dist of 35.8 ft. scribed T2N, R40E, S22BT;  
All distances measured to BT scribe.

I stamped the disk.



County Surveyor  
Office of Oregon

State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 20 day of July 1973, at 11 o'clock P.m. (signed)

*James G. Voelz*  
(COUNTY OFFICIAL)

County of Union

DATE RECEIVED \_\_\_\_\_ (DEPUTY)

DATE FILED \_\_\_\_\_

By \_\_\_\_\_

File No. 303-83R

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*James G. Voelz*  
OREGON  
MAY 4, 1956  
JAMES G. VOELZ  
381