

Dependent Resurvey of a Portion of the South Boundary of
the Umatilla Indian Reservation,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

1.105 The closing cor. of secs. 33 and 34, for the north side of the
Reservation boundary, hereinafter described.

N. 89° 35' 30" W., beginning ~~new~~ measurement.

Over level prairie.

4.50 Enter timber and light undergrowth; begin descent over SW. slope.

34.840 The 65 Mile Corner on the S. bdy. of the Umatilla Indian
Reservation, perpetuated and recorded by Barry B. Barbour,
Registered Land Surveyor No. 1051, in 1980, monumented with an
iron post, 2 ins. diam., firmly set, protruding 10 ins. above
ground, with brass cap mkd.

T 2 S R 34 E

U I R

65M

1917

from which the remains of the original bearing trees

A lodgepole pine stump, 18 ins. diam., bears S. 57° E.,
18 lks. dist., no marks visible. (Record, S. 69° E.,
9 lks.)

A lodgepole pine snag, 14 ins. diam., bears S. 55° W.,
24 lks. dist., with scribe marks UIR M on rotted blaze.
(Record, S. 52° W.)

and the remains of bearing trees mkd. by Wilkes

A root hole, bears N. 87° E., 54 lks. dist., alongside
of which is lying a lodgepole pine, 10 ins. diam.,
with scribe marks BT on rotted blaze.

A lodgepole pine snag, 12 ins. diam., bears N. 48½° W.,
42½ lks. dist., with scribe marks UIR 65M BT on
partially healed blaze. (Record, N. 51° W., 44 lks.)

and bearing trees mkd. by Barbour

A fir, 14 ins. diam., bears N. 7½° E., 47 lks. dist.,
with scribe marks UIR MP 65 BT and a nail and washer
at base of partially healed blaze.

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By *[Signature]* DEPUTY

File No. 220-2013R

Dependent Resurvey of a Portion of the South Boundary of
the Umatilla Indian Reservation,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

A fir, 10 ins. diam., bears S. $74\frac{1}{2}^{\circ}$ E., $39\frac{1}{2}$ lks. dist.,
with scribe marks UIR MP 65 BT and a nail and washer
at base of partially healed blaze.

S. $89^{\circ} 48' 00''$ W., on the 66th mile.

Ascend broken NE. slope, through timber and light undergrowth.

5.630 Point for the closing cor. on the N. and S. center line of sec.
33, for that portion of the section north of the Reservation
boundary, hereinafter described.

25.550 Point for the closing cor. on the N. and S. center line of the
SW $\frac{1}{4}$ of sec. 33, for that portion of the section north of the
Reservation boundary, hereinafter described.

29.85 Top of ascent; thence over level ground.

39.835 The 65 $\frac{1}{2}$ Mile Corner on the S. bdy. of the Umatilla Indian
Reservation, perpetuated and recorded by Barry B. Barbour,
Registered Land Surveyor No. 1051, in 1980, monumented with an
iron post, 2 ins. diam., firmly set, protruding 10 ins. above
ground, with brass cap mkd.

T 2 S R 34 E
UIR
65 $\frac{1}{2}$ M
1917

from which the remains of the bearing trees mkd. by Wilkes

A larch snag, 9 ins. diam., bears N. 43° E., 19 lks.
dist., with healed blaze. (Record, 18 lks.)

A larch, 14 ins. diam., bears S. $55\frac{1}{2}^{\circ}$ E., 10 lks.
dist., no marks visible. (Record, S. 57° E., 9 lks.)

and a bearing tree mkd. by Barbour

A larch, 17 ins. diam., bears N. 46° E., $43\frac{1}{2}$ lks. dist.,
with scribe marks UIR MP 65 $\frac{1}{2}$ BT and a nail and washer
at base of partially healed blaze.

The corner is located on NW. slope, 5 lks. N. of a barbed wire
fence, 4 strands, bears generally E. and W.

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DEPUTY

File No. 200-2013R

Retracement-Resurvey of the South Boundary
Original Umatilla Indian Reservation

Chains

from the original bearing trees. At exact cor. point
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for 63 $\frac{1}{2}$ Mile Cor., with brass cap marked

UNION COUNTY
SURVEYOR

UIR
63 $\frac{1}{2}$ M
1917

Date Received 3/11/13Date Filed 3/11/13By M. L. DerryFile No. 267-2013R

from which

A tamarack, 20 ins. diam., bears S.45°E., 62 lks.
dist., marked in bark. I remark in the wood, 63 $\frac{1}{2}$
M U R B T (old B.T.)
A lodgepole pine, 12 ins. diam., bears N.46°W., 36
lks. dist., marked $\frac{1}{2}$ M U R B T. (old B.T.)

Thence

S.89°56'E., on a true line, resurveying east half of 64th
Mile.

41.90 Dry gulch, course SE.; ascend gradually on SW. slope, 100
ft. to

51.79 Top of ridge, descends S.; descend 150 ft. to

65.68 Dry gulch, 3 lks. wide, course S.20°W.; ascend 180 ft. to

80.39 The 63 Mile Cor., heretofore described.

Land, mountainous, not very rough.

Soil, light loam, shallow, on basalt bedrock; 2nd and 3rd
rate.

Timber, yellow pine, lodgepole pine and fir.

Undergrowth, lodgepole pine, balsam and willow.

From the 64 Mile Cor.

West, retracing the 65th Mile

40.36 Pass 10 lks. N. of the 64 $\frac{1}{2}$ Mile Cor., hereinafter described.

80.37 Fall 28 lks. S. of the 65 Mile Cor., the position of which
is determined from the original bearing trees. At the
exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for 65 Mile Cor., with brass cap marked

T2SR34E
UIR
65M
1917

5720

Retracement-Resurvey of the South Boundary
Original Umatilla Indian Reservation

Chains

from which

- A lodgepole pine, 8 ins. diam., bears S.69°E., 9 lks. dist., marked U R 65 M B T (old B.T., now fallen)
- A lodgepole pine, 8 ins. diam., bears S.52°W., 24 lks. dist., marked U R 65 M B T (old B.T.)
- A lodgepole pine, 8 ins. diam., bears S.85°W., 27 lks. dist., marked U R 65 M B T (old B.T., now dead)
- A lodgepole pine, 8 ins. diam., bears S.79°E., 27 lks. dist., marked U I R 65 M B T (new B.T.)
- A lodgepole pine, 9 ins. diam., bears N.51°W., 44 lks. dist., marked U I R 65 M B T (new B.T.)
- A lodgepole pine, 7 ins. diam., bears N.67°E., 54 lks. dist., marked U I R 65 M B T (new B.T.)

thence

S.89°27'E., on a true line, resurveying 65th Mile.

Over mountainous land, through dense small timber.

A fence follows close to line.

Descend 100 ft. to

15.32 Jennings Creek bed, 30 lks. wide, course SSE., water in holes.

Leave dense small timber; enter scattering large timber.

Ascend 340 ft. to

54.87 Intersect line bet. secs. 33 and 34, at the closing cor., which is a basalt stone, 1 1/2 x 9 x 4 ins., marked U R on N. and C C on E. faces, in mound of stone, 6 ins. high.

At a point 1 lk. N. of old closing cor.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for witness cor. to the closing cor. of secs. 33 and 34, with brass cap marked

C C
T2S R34E
UIR
S33 | S34
WC
1917

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

**UNION COUNTY
SURVEYOR**

Date Received 3/11/13

Date Filed 3/11/13

By [Signature] DEPUTY

File No. 267-2013R