

443

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

~~and bearing trees mkd. by Barbour~~

~~A ponderosa pine, 17 ins. diam., bears S. 58 $\frac{3}{4}$ $^{\circ}$ E.,
24 lks. dist., with illegible scribe marks on
partially healed blaze.~~

~~A fir, 17 ins. diam., bears N. 81 $\frac{1}{2}$ $^{\circ}$ W., 54 $\frac{1}{2}$ lks. dist.,
with illegible scribe marks on partially healed blaze.~~

From this same point, the SE. cor. of the Umatilla Indian
Reservation, perpetuated and recorded by Barry B. Barbour,
Registered Land Surveyor No. 1051, in 1980, bears
S. 20 $^{\circ}$ 30' 30" W., 6.865 chs. dist., monumented with an iron
post, 2 ins. diam., firmly set, protruding 12 ins. above ground,
with brass cap mkd.

T 2 S R 34 E
SE COR
UIR
1917

J2S34
SEUR

from which the remains of the bearing trees mkd. by Wilkes

A fir stump, 18 ins. diam., bears N. 10 $\frac{1}{2}$ $^{\circ}$ E., 43 lks.
dist., with illegible scribe marks on rotted blaze.
(Record, N. 13 $\frac{1}{2}$ $^{\circ}$ E.)

A root hole, bears S. 40 $\frac{3}{4}$ $^{\circ}$ E., 26 lks. dist., with
rotted pine, size indeterminate, lying alongside,
with scribe marks UR BT on partially healed blaze.

and bearing trees mkd. by Barbour

A larch, 16 ins. diam., bears S. 13 $^{\circ}$ E., 70 $\frac{1}{2}$ lks. dist.,
with scribe marks UIR SE COR BT and a nail and washer
at base of partially healed blaze.

A larch, 14 ins. diam., bears N. 16 $^{\circ}$ W., 28 $\frac{1}{2}$ lks. dist.,
with scribe marks UIR SE COR BT and a nail and washer
at base of partially healed blaze.

From the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.

N. 0 $^{\circ}$ 18' 30" E. bet. secs. 35 and 36.

~~Over level ground, through timber and light undergrowth.~~

~~Abandoned dirt road, 15 lks. wide, bears N. 80 $^{\circ}$ W. and S. 60 $^{\circ}$ E.~~

UNION COUNTY
SURVEYOR

38.00

Date Received 3/8/13

Date Filed 3/8/13

By *[Signature]*

Form 9600-10a (November 1987) USDI-BLM

FIELD NOTE PAPER

File No. 214-2013R

Retracement-Resurvey of the East Boundary

Original Umatilla Indian Reservation

Chains

Descend 90 ft. to
 46.10 Dry gulch, course NW.; ascend 40 ft. to
 50.66 Pass 40 lks. N.70°W. of old cabin on top of ridge, descending
 NW.
 54.64 Dry gulch, course W.; ascend 200 ft. to
 60.78 Top of ascent; enter bench land, bears NW. and SE.
 60.05 The 61 Mile Cor., heretofore described.

Land, mountainous.
 Soil, light loam, gravelly, shallow, over basalt bedrock;
 2nd rate.

Timber, pine, fir and tamarack.
 Undergrowth, pine, fir, tamarack and willow.

From the 62 Mile Cor.
 S. 80°00'W., retracing the 63rd Mile

39.81 Pass 10 lks. S.70°E. of the 62½ Mile Cor., hereinafter
 described.

47.86 Fall 16 lks. S.70°E. of Angle Cor. of Umatilla Indian
 Reservation, which is a post, now rotted off, marked as
 described by the surveyor general, the markings being
 nearly illegible. At exact cor. point
 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
 ground, for angle cor., with brass cap marked

T2S R34E
 UIR/
 1917

from which

A fir, 18 ins. diam., bears N.13°30'E., 43 lks. dist.,
 marked > U R B T (new B.T.)

A lodgepole pine, 5 ins. diam., bears S.40°45'E., 26
 lks. dist., marked > U R B T (new B.T.)

A fir, 8 ins. diam., bears S.25°W., 13½ lks. dist.,
 marked U R B T (old B.T.)

Thence

N.20°25'E., on a true line resurveying the 63rd Mile.

6.85 Intersect line bet. secs. 35 and 36, at the closing cor.

**UNION COUNTY
 SURVEYOR**

Date Received 3/11/13

Date Filed 3/11/13

By JGL Deputy

File No. 260-2013R


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. SE UIR

History of original corner establishment:

Corner was recovered by L. Wilkes, survey group No. 38, during October, 1917. Surveyor General's notes state: "Set an iron post, 3 ft. long, 2 ins. diam., 34 ins. in the ground, for angle cor., with brass cap marked:

T2S R34E
UIR
1917



from which: A fir, 18 ins. diam. bears N13°30'E., 43 lks. dist. marked URBT (new B.T.). A lodgepole pine, 5 ins. diam. bears S40°45'E., 26 lks. dist. marked URBT (new B.T.). A fir, 8 ins. diam., bears S25°W, 13 1/2 lks. dist. marked UR BT (old B.T.)."

Description of corner evidence found:

Found 2" iron pipe and brass cap projecting 9" above the ground. From which by magnetic declination of N20°E; A dead and down lodgepole pine, bears S45°E, 17.9 ft. with some scribing.

Marked:
T2S R34E
SECOR
UIR
1917

Description of monument and accessories I established to perpetuate the original location of this corner:

From which I add; A 15" tamarac bears S06°W, 47.9 ft, scribed UIR SE COR BT. A 15" tamarac bears N23°W, 18.8 ft. scribed UIR SE COR BT. Painted blazes red and 6" red band around. Placed 54-3s, 54-4s and brass washers stamped PLS 1051 on BTs. Placed 54-2 and 54-4 on steel fence post 5' west and 54-2 on steel fence post N20°E, 5' of the corner.

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland
Douglas Moser
Ronald Gilroy

November 11, 1980

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Barry B. Barbour
OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

UNION COUNTY SURVEYOR
Date Received _____
Date Filed _____
By _____
NARRATIVE DRAWING 1/3
File No. _____

REFER TO SURVEY 10-81

Office of...County Surveyor..... County of...Union.....
State of Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 30th day of January....., 1981.

..... by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

UNION COUNTY SURVEYOR
☆ GPO-798-276
Date Received 3/12/13
Date Filed 3/12/13
By *[Signature]* DEPUTY
File No. 284-2013R