

Retracement-Resurvey-of the South Boundary
Original Umatilla Indian Reservation

Chains

A tamarack, 5 ins. diam., bears N.47°E., 27 lks. dist., marked U I R 66½ M B T (new B.T.)

Whence

S.89°52'E., continuing my measurements

Descend gradually.

54.89 A spring, flowing SE., bears South, 25 lks. dist.

Ascend gradually.

60.80 The 66 Mile Cor., heretofore described.

Land, mountainous, near top of high ridge, not very rough.

Soil, shallow; 2nd rate.

Timber, yellow pine, tamarack, fir and lodgepole pine.

Undergrowth, lodgepole pine on N. slope and balsam and willow.

From the 67 Mile Cor.

West, retracing the 68th Mile.

40.37 Pass 15 lks. N. of the 67½ Mile Cor., hereinafter described.

45.40 Fall 20 lks. N. of angle cor., which is an old post, 3x5 ins. sq., 30 ins. above ground, marked U R on E., ½ on S. face; no stone or mound of stone near the post. At exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for angle cor. of Umatilla Indian Reservation, with brass cap marked

T2S
R33E R34E
SW COR
UIR

1917

from which

A fir, 6 ins. diam., bears N.35°W., 13 lks. dist., marked \wedge U I R B T (new B.T.)

A fir, 8 ins. diam., bears N.46°E., 45 lks. dist., marked \wedge U I R B T (new B.T.)

A pine, 36 ins. diam., bears S.25°W., 54 lks. dist., marked U R \wedge B T (old B.T. not mentioned in

**UNION COUNTY
SURVEYOR**

Date Received 3/11/13

Date Filed 3/11/13

By J. G. & Co. Deput.

File No. 261-2013R

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


Index File No. SW COR UIR X-Y-1

History of original corner establishment:

Corner was recovered by L. Wilkes, survey group No. 38, in October, 1917. "Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground, for angle cor. of Umatilla Indian Reservation, with brass cap marked:

- from which:
- A fir, 8 ins. diam., bears N35°W, 13 lks. dist. marked L UIR BT (new BT).
- A fir, 8 ins. diam., bears N46°E, 45 lks. dist. marked L UIR BT (new BT).
- A pine 36 ins. diam., bears S25°W, 54 lks. dist. marked L UIR BT (old BT not mentioned in field notes)."

T2S
R33E R34E
SW COR
UIR
1917



Description of corner evidence found:

Found 2" iron pipe and brass cap marked:
 Pipe projecting 12" above the ground, but loosely set.
 Removed 12" of duff and replaced with dirt. Built mound of stone around to cap.
 From which by magnetic declination of N20°E:
 A 30" pine bears N50°W, 18.2 ft. with open blazes and visible scribing.
 A 15" fir bears N45°E, 32.7 ft. with grown over blazes. Painted 6" red band around the BTs. Placed 54-3s and 54-4s. Placed 54-2 and 54-4 on a steel fence post 5' east and placed 54-2 on a steel fence post 5' south of the corner.

T2S
R34E
R33E SW COR
UIR
1917

Note: Pipe stamped R33E. Notes state R33 1/2 E.

Description of monument and accessories established to perpetuate the original location of this corner:

I hereby certify that the above monument was recovered by me and the above work done to perpetuate the original evidence.

Witnesses: Daniel Rowland
Doug Moser
Ron Gilroy

November 6, 1980

REGISTERED PROFESSIONAL LAND SURVEYOR

Barry B. Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

UNION COUNTY SURVEYOR

Date Received _____

Date Filed _____

By _____

NARRATIVE DRAWER 1/3
File No. _____

REFER TO SURVEY 10-81

Office of..... County Surveyor..... County of..... Union.....
 State of..... Oregon....., I hereby certify that the within instrument was filed in this office
 for record on the... 30th day of... January... , 19 81
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

☆ GPO-798-276
Date Received 3/12/13

Date Filed 3/12/13

By [Signature] DEPUTY

File No. 286-2013R