

Subdivision of Section 34,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

**UNION COUNTY
SURVEYOR**

Date Received 3/8/13

Date Filed 3/18/13

By [Signature] DEPUTY

File No. 242-2013R

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

C
N 1/16 | S 34
C
1987

from which

A ponderosa pine, 8 ins. diam., bears S. 56½° E.,
44½ lks. dist., mkd. CN 1/16 S34 BT.

A fir, 12 ins. diam., bears S. 45½° W., 75½ lks. dist.,
mkd. CN 1/16 S34 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.

The corner is located on SE. slope.

26.00 Dirt road, 15 lks. wide, bears N. 60° E. and S. 55° W.

29.80 Ravine, drains S. 70° E.

38.40 Ravine, drains N. 55° E.

39.850 Point for the center ¼ sec. cor. of sec. 34, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T 2 S R 34 E
C ¼ S 34
1987

from which

A ponderosa pine, 23 ins. diam., bears S. 17½° E.,
150½ lks. dist., mkd. C¼ S34 BT.

A fir, 16 ins. diam., bears S. 48½° W., 72 lks. dist.,
mkd. C¼ S34 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.

40.20 Dirt road, 15 lks. wide, bears N. 60° E. and S. 60° E.