


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. X-21

History of original corner establishment:

Corner was originally established by Currin & Noland under GLO contract, on July 16, 1887. Surveyors General's notes state: Set a post 3 ft. long 3 ins. square 24 ins. in the ground for 1/4 sec. cor. marked 1/4S on W face, from which: A fir 16 ins. diam. bears S 70°E 25 lks. dist. marked 1/4S BT. A fir 18 ins. dia. bears N25°W, 40 lks. dist. marked 1/4S BT."



Description of corner evidence found:

Found 3" x 24" scribed wood post from which: A 20" fir snag bears N67°E, 2.0 ft. A 24" green fir bears S36°W, 23.0 ft. with grown over blazes and bark scribed 1/4. Post was set in mound of stone.

Description of monument and accessories established to perpetuate the original location of this corner:

At center of post set 2 1/2" X 30" galvanized pipe and brass cap marked; Set pipe 24" in the ground and mound of stone around to cap,

From which by magnetic declination of N20°E;

A 24" tamarac bears S82°E, 36.4 ft. scribed 1/4S36 BT.

Placed 54-3s and 54-4s on old BTs. Painted blazes red and 6" red band around.

Placed 54-3, 54-4 and brass washers stamped PLS 1051 on BTs. Placed 54-4 on steel fence post 5' south of the corner.

T2S R34E
1/4
S35 + S36
OR PLS 1051
1980

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses; Daniel Rowland
Doug Moser

October 15, 1980

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Barry B. Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

Office of County Surveyor..... County of Union
State of Oregon..... I hereby certify that the within instrument was filed in this office
for record on the 30th day of January....., 1981

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR
Received _____
Filed _____ GPO-798-276
By _____
File No. 195-84R

441

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by James P. Currin and James E. Noland,
in 1887, and the resurvey by Lincoln L. Wilkes, in 1917)

From the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, perpetuated and recorded
by Barry B. Barbour, Registered Land Surveyor No. 1051, in 1980,
monumented with an iron post, 2 ins. diam., firmly set,
protruding 6 ins. above ground, in a collar of stone, with brass
cap mkd.

T 2 S R 34 E
 $\frac{1}{4}$
S 35 | S 36
OR PLS 1051
1980

T2S34
X21

from which an original bearing tree

A larch, 17 ins. diam., bears S. $79\frac{1}{2}^{\circ}$ E., 55 lks. dist.,
with scribe marks $\frac{1}{4}$ S36 BT on chopped open blaze.
(Record, fir, S. 70° E., 25 lks.)

and a bearing tree mkd. by Wilkes

A fir, 16 ins. diam., bears N. 80° E., 2 lks. dist.,
no marks visible on partially healed, rotted blaze.

and the remains of a bearing tree of no known record

A fir snag, 22 ins. diam., bears S. 38° W., 35 lks. dist.,
with illegible scribe marks on bark.


S. $2^{\circ} 27' 00''$ W., bet. secs. 35 and 36.

Over level ground, through timber and light undergrowth.

3.915

Intersect the E. bdy. of the Umatilla Indian Reservation at the
original closing cor. of secs. 35 and 36, designated as the
closing cor. for both sides of the Reservation boundary by Wilkes
in 1917, perpetuated and recorded by Barry B. Barbour, Registered
Land Surveyor No. 1051, in 1980, monumented with an iron post, 2
ins. diam., firmly set, protruding 8 ins. above ground, with
brass cap mkd.

T2S34
X21E



UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DERBY

File No. 252-2013R