

Dependent Resurvey of a Portion of the South Boundary of
the Umatilla Indian Reservation,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

BLAZE

N. 89° 25' 00" W., beginning new measurement.

3.855

The closing cor. of secs. 32 and 33, for the south side of the
Reservation boundary, perpetuated and recorded by Barry B.
Barbour, Registered Land Surveyor No. 1051, in 1980,
reestablished from Wilkes' bearing trees. This corner was
erroneously established by Wilkes as the closing cor. of secs. 32
and 33 for the north side, monumented with an iron post, 2 ins.
diam., firmly set, protruding 4 ins. above ground, with brass cap
mkd. T2S R34E CC S32 S33 CC S32 S33 OR PLS 1051 1980, from which
the remains of the bearing trees mkd. by Wilkes:

A larch snag, 15 ins. diam., bears N. 48½° E., 43 lks.
dist., with scribe marks CC T2S R34E S33 BT on partially
healed blaze.

A larch, 26 ins. diam., bears N. 20½° W., 97 lks. dist.,
with healed blaze.

and bearing trees mkd. by Barbour

A fir, 10 ins. diam., bears N. 73° E., 61 lks. dist.,
with scribe marks T2S R34E S BT and a nail and
washer at base of partially healed blaze.

A fir, 12 ins. diam., bears S. 63° E., 68½ lks. dist.,
with scribe marks T2S R34E S33 CC BT and a nail and
washer at base of partially healed blaze.

A larch, 14 ins. diam., bears S. 63° W., 75½ lks. dist.,
with scribe marks T2S R34E S32 CC BT and a nail and
washer at base of partially healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 2 S R 34 E
S 32 | S 33
C | C
1987

Deposit a white "DEEP-1" magnetic marker at the base and the iron
post alongside the stainless steel post.

**UNION COUNTY
SURVEYOR**

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] PEPL

File No. 254-2013R

Dependent Resurvey of a Portion of the South Boundary of
the Umatilla Indian Reservation,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

From this point, the cor. erroneously identified by Wilkes as the original closing cor. for the north side, bears South, 0.090 chs. dist., a larch snag, 9 ins. diam., with illegible scribe marks on partially healed blaze, facing N.

N. 89° 02' 30" W., beginning new measurement.

Descend NW. slope.

- 1.775 True point for the closing cor. of secs. 32 and 33, for the north side of the Reservation boundary, hereinafter described.
- 21.45 McCoy Creek, dry, 20 lks. wide, drains N. 15° E.; asc. E. slope.
- 35.665 The 66 Mile Corner on the S. bdy. of the Umatilla Indian Reservation, perpetuated and recorded by Barry B. Barbour, Registered Land Surveyor No. 1051, in 1980, monumented with an iron post, 2 ins. diam., firmly set, protruding 24 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 2 S R 34 E

UIR

66M

RESET 1051

1980

1917

from which the remains of the original bearing trees

A root hole, bears S. 73° E., 66 lks. dist., with remnants of a rotted pine lying alongside, with scribe marks BT.

A root hole, bears N. 33° W., 31 lks. dist., with remnants of a rotted fir lying alongside.

and bearing trees mkd. by Barbour

A ponderosa pine, 18 ins. diam., bears N. 33½° E., 94½ lks. dist., with scribe marks UIR MP 66 BT and a nail and washer at base of partially healed blaze.

A fir, 16 ins. diam., bears S. 30½° E., 101 lks. dist., with scribe marks UIR MP 66 BT and a nail and washer at base of partially healed blaze.

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By ALL DEPUTY

File No. 254-20132