

Dependent Resurvey of a Portion of the South Boundary of
the Umatilla Indian Reservation,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

4.690

The closing cor. of secs. 34 and 35, for the south side of the Reservation boundary, established and recorded by Barry B. Barbour, Registered Land Surveyor No. 1051, in 1980, and is accepted as the corner, monumented with an iron post, 2 ins. diam., firmly set, protruding 4 ins. above ground, with brass cap mkd.

T 2 S R 34 E

UIR

S 34 | S 35

C | C

OR PLS 1051

1980

from which a bearing tree mkd. by Barbour

A fir, 13 ins. diam., bears S. $63\frac{1}{2}^{\circ}$ W., $30\frac{1}{2}$ lks. dist., with scribe marks T2S R34E S34 CC BT on partially healed blaze.

From this corner, the original closing cor. of secs. 34 and 35 for the south side of the Reservation boundary, bears S. $0^{\circ} 45' 00''$ E., 0.075 chs. dist., monumented with an iron pipe, 2 ins. diam., firmly set, protruding 10 ins. above the ground, with brass cap mkd. T2S R34E UIR S34 S35 CC 1917, from which the remains of the original bearing trees:

A fir, 38 ins. diam., bears S. 9° E., 38 lks. dist., with upper and lower healed blazes.

A fir stump, 30 ins. diam., bears S. $89\frac{1}{2}^{\circ}$ W., 71 lks. dist., no marks visible. (Record, S. 70° W., 72 lks.)

Mark the brass cap AM and bury the iron post in place.

N. $89^{\circ} 40' 30''$ W., beginning new measurement.

- 0.590 True point for the closing cor. of secs. 34 and 35, for the north side of the Reservation boundary, hereinafter described.
- 12.10 Spur, slopes N.
- 12.65 Descend S. 70° W. slope.
- 18.95 Creek, dry, 2 lks. wide, drains S. 40° W.; continue over level creek bottom.

UNION COUNTY
SURVEYOR

Date Received 3/8/13Date Filed 3/8/13BY [Signature] DEPUTYFile No. 257-2013R

417I

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


Index File No. X-Y-17-S

History of original corner establishment:

Corner was originally established by L. Wilkes, survey group No. 38, during October, 1917. Surveyor General's notes state: "Set an iron post, 3 ft. long, 2 ins. diam, 12 ins. in the ground and 12 ins. in mound of stone, for closing corner of secs. 34 and 35, with brass cap marked

T2S R34E
UIR

S34 S35
C C
1917



from which:

A fir, 24 ins. diam., bears S9°E, 36 lks. dist. marked CC T2S R34E S35 BT.
A fir, 12 ins. diam., bears S70°W, 72 lks. dist. marked CC T2S R34E S34 BT."

Description of corner evidence found:

Found 2" iron pipe and brass cap as described above. From which a 44" fir bears S08°E, 25.0 ft. with grown over blazes. A 36" fir stump bears S72°W, 47.4 ft., cut below blazes.

Description of monument and accessories I established to perpetuate the original location of this corner:

From the above brass cap measured N0°30'W, 5.09 ft. and set 2 1/2" X 30" galvanized pipe and brass cap marked: Pipe set on UIR line, 25" in the ground. From which by magnetic declination of N20°E: A 14" white fir bears S65°W, 20.2 ft. scribed T2S R34E S34 CC BT. Painted blazes red and 6" red band around. Placed 54-3, 54-4 and brass washer stamped PLS 1051 on the BT. Placed 54-3s and 54-4s on the old BTs. Placed 54-2 and 54-4 on a steel fence post 5' east of the corner.

T2S R34E
UIR
S34 S35
C C
OR PLS 1051
1980

I hereby certify that the above corner monument was established as herein described.

Witnesses: Daniel Rowland
Doug Moser

October 29, 1980

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Barry B. Barbour
OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

UNION COUNTY SURVEYOR

Date Received _____

Date Filed _____

By NARRATIVE DRAWER 1/3

File No. _____

REFER TO SURVEY 10-81

Office of _____ County Surveyor _____ County of _____ Union
Oregon
State of _____, I hereby certify that the within instrument was filed in this office
for record on the...30th day of...January....., 19.81

(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)

UNION COUNTY SURVEYOR

Date Received 3/12/13

Date Filed 3/12/13

By [Signature] DEPUTY

File No. 288-2013R