
History of original corner establishment:

Corner originally established by John A. Hurlburt under GLO contract number 201, dated August 5, 1873. Surveyor General record states:
Set pine post 4 ft. long 3 in. thick 2 ft. in ground for % sec. cor.
Fir 15 in. dia. N24°E 42 lks
Pine 36 in. dia. S69°W 70 lks



No record of subsequent monumentation found in Union County survey records. Description of corner evidence found:

Found the rotted remains of the original corner post to a depth of 8 inches.

Found no remains of the original Northeast bearing tree.

Found a 36 inch diameter Ponderosa Pine stump S69°W. 70 lks. rotted with scribes visible.

See map of survey dated November, 1989.

Description of monument and accessories I established to perpetuate the original location of this corner:

In place of the found original corner post, I set a 2½" x 30" aluminum pipe with aluminum cap marked as shown, 28 inches in the ground, from which:

1-10


New Bearing Trees: A 12 inch diameter Douglas Fir bears S67°W. 13.04 feet marked ½ S13 BT A 21 inch diameter Ponderosa Pine bears N66°W. 34.24 feet marked ½ S13 BT

Painted a 6 inch red band around all BTs and attached bearing tree and land survey monument signs.

Set a steel fencepost approximately 5 feet North with land survey monument sign attached.

I hereby certify that the above corner point was perpetuated as hereon described on October 1, 1989.





I used a steel tape and magnetic compass in the establishment of new accessories. I used 17° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

	County of , I hereby certify that the within inst	
for record on the day o		T
(COUNTY OFFICE	SURVEYOR	(DEPUTY)
Form R6-7100-57 (9/71)	Data Encoived 12-27-89 \$0	B. GOVERNMENT PRINTING OFFICE - 1983-793-276
	Data Filed 12-27 (84)	L-25
	By R. ROBINEON, DONLY	·
	NON. 213-84R	