
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner originally established by John A. Hurlburt under GLO contract number 201, dated August 5, 1873. Surveyor General record states: Set pine post 4 ft. long 3 in. thick 2 ft. in ground for 4 sec. cor. Pine 30 in. dia. South 38 lks Pine 8 in. dia. North 47 lks



No record of subsequent monumentation found in Union County survey records. Description of corner evidence found:

Found no evidence of the original corner or its accessories. See map of survey dated June, 1989.

UNION COUNTY SURVEYOR
Dato Received 8-22-89
0ato Filod 8-22-89
BY G. LANGLIZ, DERUTY
File No. 125-89 R

Description of monument and accessories I established to perpetuate the


original location of this corner: At position determined by survey, 1 set a $2\frac{1}{2}$ " x 30" aluminum pipe with aluminum cap marked as shown, 38 inches in the ground, 8 inches below the surface of a forest road, from which:

New BTs: A 14 inch diameter Ponderosa Pine bears S55°E, 31.97 feet marked ¼ S24 BT A 10 inch diameter Douglas Fir bears N7°W, 22.75 feet marked ¼ S13 BT

Painted a 6 inch red band around all BTs and attached bearing tree and land survey monument signs.

Set a steel fencepost approximately 3.6 feet South with land survey monument sign attached.

I hereby certify that the above corner point was perpetuated as hereon described on May 24, 1989. Witness: Rick Robinson





I used a steel tape and magnetic compass in the I used a steel tape and magnetic compass in the establishment of new accessories. I used 17° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

(DEPUTY)

Office of	County of
State of	, I hereby certify that the within instrument was filed in this office
	······ , 19
	by

(COUNTY OFFICIAL)

Form R6-7100-57 (9/71)

☆ GPO 799-509