
History of original corner establishment:

Corner originally established by Henry Meldrum under GLO contract number 450. dated June 11, 1882. Surveyor General record states:

Set basalt stone 24x12x8 ins. 18 in. in ground for $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ on N face, from which:

A Fir 20 in diam bears N33°W 34 lks dist marked \S BT A Pine 24 in diam bears S48°W 83 lks dist marked \S BT



No record of subsequent monumentation found in Union County survey records.

Description of corner evidence found:

Found a stone 20x12x8 inches marked $\frac{1}{4}$ set in a mound of stone.

Found a 24 inch diameter Ponderosa Pine S48°W. 45 feet, loose on the ground with scribes visible.

Found a 34 inch diameter Douglas Fir N33°W, 34 lks, dead and down with scribes visible.

See map of survey dated November, 1989.

Description of monument and accessories I established to perpetuate the

original location of this corner: In place of the found original corner stone, I set a 2½" x 30" aluminum pipe with aluminum cap marked as shown, 22 inches in the ground, from which:

New Bearing Trees; A 10 inch diameter Ponderosa Pine bears N38°E, 68.5 feet marked ¼ S18 BT A 12 inch diameter Ponderosa Pine bears S15°E, 92.08 feet marked ¼ S19 BT

Painted a 6 inch red band around all BTs and attached bearing tree and land survey monument signs. Set a steel fencepost approximately 5 feet North with land survey monument and property boundary signs attached. Buried the original corner stone North and alongside of monument. Raised a mound of stone around monument, 3 ft. base to top of cap.

I hereby certify that the above corner point was perpetuated as hereon described on October 2, 1989.

Witness: Rick Robinson

GAIFFITH T2S **R37E** S 18 S 19 1989 **OPLS 644**

OREGON JULY 10, 1964 DUANE I. GRIFFITH

REGISTERED **PROFESSIONAL** AND SURVEYOR

I used a steel tape and magnetic compass in the establishment of new accessories. I used 17° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

Office of...... County of..... I hereby certify that the within instrument was filed in this office for record on the day WELL DN .. COUNTY 19..... SURVEYOR, (COUNTY OFFICIALIA (DEPUTY)

Form R6-7100-57 (9/71)

Poto Roccived 12-27-89 Prior Filed 12-27-89

File No.

\$U.S. GOVERNMENT PRINTING OFFICE - 1983 -793 - 271

N - 03

1 - 23