

T3S33½A21

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 33½ E., Willamette Meridian, Oregon

UNION COUNTY SURVEYOR	
Date Received	<u>3/15/13</u>
Date Filed	<u>3/15/13</u>
By	<u>J. L. Deputy</u>
File No.	<u>362-2013R</u>

CHAINS

A fir, 19 ins. diam., bears N. 75° W., 31½ lks.
dist., mkd. T2S R33E S36 BT.

Deposit corner stone alongside iron post.

North Boundary, T. 3 S., R. 33½ E.,
Willamette Meridian, Oregon

(Remonumenting a corner established by Rufus S. Moore,
U. S. Deputy Surveyor, in 1882)

The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, on the N. bdy. of the
Tp., monumented with the original unmarked basalt stone,
16 x 16 x 3 ins., loosely set in a mound of stone, 2 ft.
base, 1 ft. high, from which the only remaining original
bearing tree:

A pine, 25 ins. diam., bears S. 41° E., 202 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 2 S R 33 E
S 36
S 1
T 3 S R 33½ E
1977

from which a new bearing tree

A pine, 12 ins. diam., bears N. 50° E., 43 lks.
dist., mkd. $\frac{1}{4}$ S36 BT.

Deposit corner stone alongside iron post.

(Remonumenting a corner established by Rufus S. Moore,
U. S. Deputy Surveyor, in 1882,
and redescribed by John C. Arnold,
U. S. Deputy Surveyor, in 1891)

The cor. of secs. 1, 2, 35, and 36, monumented with the
original basalt stone, 16 x 10 x 10 ins., firmly set 10
ins. in the ground, mkd. with 1 notch on E. and 2 notches
on W. edges, from which the remains of the original
bearing trees:

A pine snag, 11 ins. diam., bears S. 56° W., 36
lks. dist., with scribe marks T3S R33½E S2 BT
visible on open blaze. (Record, S. 50° W.)

A pine snag, 24 ins. diam., bears N. 48° W., 37
lks. dist., with scribe marks R33½E S35 visible
on open and burned blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 33½ E., Willamette Meridian, Oregon

CHAINS

T 2 S R 33 E
S 35 S 36
S 2 S 1
T 3 S R 33½ E
1977

from which new bearing trees

A grand fir, 9 ins. diam., bears N. 42° E., 20 lks. dist., mkd. T2S R33E S36 BT.

A grand fir, 12 ins. diam., bears S. 70° E., 12 lks. dist., mkd. T3S R33½E S1 BT.

A grand fir, 12 ins. diam., bears S. 43° W., 17½ lks. dist., mkd. T3S R33½E S2 BT.

A grand fir, 15 ins. diam., bears N. 56½° W., 31 lks. dist., mkd. T2S R33E S35 BT.

Deposit corner stone alongside iron post.

Subdivisions, T. 3 S., R. 33½ E.,
Willamette Meridian, Oregon

(Remonumenting corners established by Rufus S. Moore,
U. S. Deputy Surveyor, in 1882)

The cor. of secs. 1, 2, 11, and 12, determined at record bearing and distance from the remains of the original bearing trees:

A fir, 18 ins. diam., bears S. 10° W., 7 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A fir, 16 ins. diam., bears N. 37° W., 17 lks. dist., with scribe marks 3S R33E S visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 3 S R 33½ E
S 2 S 1
S 11 S 12
1977

from which new bearing trees

A fir, 7 ins. diam., bears N. 34½° E., 28 lks. dist., mkd. T3S R33½E S1 BT.

A fir, 10 ins. diam., bears S. 58° E., 68 lks. dist., mkd. T3S R33½E S12 BT.

The ¼ sec. cor. of secs. 1 and 2, determined at record bearing and distance from the remains of the original bearing trees:

A pine snag, 40 ins. diam., bears N. 63° E., 102 lks. dist., with scribe marks ¼ S visible on open blaze.

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By Rufus S. L. DEPUTY

File No. 362-2013RC