


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. J-17

History of original corner establishment:

In 1882, under GLO Contract No. 451, Rufus S. Moore set a stone 12x8x6, from which a 40" Spruce bears N64°W, 42 lks.; an 8" Fir bears N38°E, 14 lks.; a 14" Fir bears S68°E, 36 lks.; and a 20" Fir bears S39°W, 10 lks.



Description of corner evidence found:

No corner monument found.

Bearing Trees Found:

- A 41" Spruce bears N4°W, 27.7 ft., blaze healed.
- An 18 1/2" Fir bears S68°E, 23.8 ft., blaze healed.
- A 25 1/2" Fir bears S39°W, 6.6 ft., blaze healed.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2 1/2" x 30" aluminum capped aluminum pipe, rising 6", stamped:

New BT:

An 11" D. Fir bearing N44°E, 32.7 ft., scribed " T3S R33E S11 BT".

T3S R33E

S10 | S11

S15 | S14

RLS 1848

1984

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6 March, 1982. Set fence post 4 ft. north of corner.

Compass Declination: 19 1/2°E

Witness: G. Arrand

From the intersection of USFS Rd. 5427 with 5427-090, northerly on 5427 one quarter mi. to newly barricaded road to the left. Follow said road westerly approx. 1/3 mi. to where road turns to the south. follow ridge northwesterly down hill. 200 ft. before the creek bottom go west to north-south creek. Corner is 10 ft. east of creek.

I hereby certify the above described corner monument and/or accessories was established as described on June 9, 1984.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

B. A. Sutton

OREGON
JULY 13, 1979
B. A. SUTTON
1848

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

(COUNTY OFFICIAL)

(DEPUTY)

**ION COUNTY
SURVEYOR**

Received 7-2-84

Date Filed ★7-3-84

By G. LANGLITZ, DEPUTY

File No. 868-84 R