CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. 3-17

History of original corner establishment:

Corner was originally established by Rufus S. Moore under GLO contract No. 461, in November, 1882. Corner was recovered in October, 1917 by L. Wilkes surveying under group #38. Surveyor General's notes state: "Commence at the cor. of secs. 2, 3, 34 and 35 on the S. bdy of the Tp., which is a volcanic stone. 12x8x12 ins. above ground, firmly set, marked with 2 notches on E. and 4 notches on W. edge; from which: A pine, 36 ins. diam. bears N72°E, 142 lks. dist., marked T 2 S R 34 E S 35 B T. DIAGRAM T2S R34E S34 | S35 S3 | S2 T3S

T2S R34E

A pine, 16 ins diam. bears S39°E., 161 lks. dist., marked T 3 S R 34 E S 2 B T. A tamarack, 28 ins. diam. bears S81°W., 85 lks. dist. marked T 3 S R 34 E S 3 B T. A tamarack, 28 ins. diam. bears N64°W, 100 lks. dist. marked T 3 S R 34 E S 34 B T."

Description of corner evidence found:

Found 20x11x8 inch stone firmly set, with 4 notches on west and 2 notches on east sides. From which: A 36" live pine, bears N78°E, 94.9 ft., visible scribing. A dead 24" pine bears S36°E, 108.0 ft., visible scribing. Á 22" tamarac snag bears S88°W, 56.6 ft., visible scribing. A 20" down tamarac bears N58°W, 67.2 ft. with full scribe.

Description of monument and accessories I established to perpetuate the original location of this corner:

S34 | S35 S3 S2 T3S OR PLS 1051 1980

At the center of the above stone set 2 1/2" X 30" galvanized pipe and brass cap marked: Set pipe 25" in the ground and placed marked stone alongside.

From which by magnetic declination of N20°E:

An 8" fir bears S82°E, 17.3 ft. scribed T3SR34ES2 BT. A 9" pine bears S 62°W, 61.1 ft. scribed T3SR34ES3 BT. A 12" tamarac bears N59°W, 124.5 ft. scribed T3SR34ES34 BT. Placed 54-3s and 54-4s on old BTs. Painted blazes red and 6" red band around. Placed 54-3s, 54-4s and brass washers stamped PLS 1051 on BTs. Placed 54-4 on steel fence post 5' north of the corner.

REGISTERED **PROFESSIONAL** LAND SURVEYOR

bows OREGON OCT. 17, 1975 BARRY B. BAI 1 0 5 1 BARBOUR

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland

Doug Moser

October 15, 1980

State ofOregon , I hereby certify that the within instrument was filed for record on the 30th day of January , 19.81		UNION COUNTY SURVEYOR
(COUNTY OFFICIAL)	(DEPUTY)	SORVETOR
Form R6-7100-57 (9/71)		Date Received
		Date Filed