CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. R-21

History of original corner establishment:

Corner was originally established by Rufus S. Moore under GLO contract No. 451 during November, 1881. Surveyors general's notes state: "A pine 40 ins, diam. marked for cor. to Secs. 23, 24, 25 and 26 marked T3S S24 on NE., 34E S23 on NW., S26 on SW and S25 on SE. faces with 2 notches on S and 1 notch E edges from which: A pine 7 ins. diam.

DIAGRAM W.C. 5.0 ft. NO. T3S R34E S23 | S24 S26 | S25

bears N30°W, 48 lks. dist. marked T3SR34ES23 BT. A pine 30 ins. diam. bears N40°E, 60 lks. dist. marked T3SR34ES24 BT. A pine 12 ins. diam. bears S48°E, 50 lks. dist. marked T3SR34ES25 BT. A pine 24 ins. diam. bears S78°W, 34 lks. dist. marked T3SR 34ES26 BT."

Description of corner evidence found:

Found 40" pine stump from which a 24" pine stump bears N42°E, 41.9 ft. scribed BT. A 17" live pine bears S54°E, 34.8 ft. scribed BT. A 24" rotten pine bears S73°W, 24.4 ft. no scribing. A 12 rotten pine stump bears N30°W, 33.0 ft. scribed BT. Compass set over nail at center of stump. No scribing on corner stump. Set W.C. 5.00 ft. north.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2 1/2" X 30" galvanized pipe and brass cap marked: Set pipe 25" in the ground and mound of stone around to cap,

From which by magnetic declination of N20°E:

W.C. 5.0 ft. No.

T3S R34E S23 | S24 S26 | S25

A 16" pine bears N54°W, 63.0 ft. scribed T3SR34ES23 BT.

A 12" pine bears N61°E, 45.7 ft. scribed T3SR34ES24 BT.

A 16" pine bears S50°W, 22.4 ft. scribed T3SR34ES25 BT.

All measurements from center of old corner stump. Painted blazes red and 6" red band around, Placed 54-3s on old and new BTs, Placed 54-4 on back of BTs. Placed brass washers stampes PLS 1051 on new BTs. Placed 54-2 and 54-4 on steel fence post 5' north of W.C.

REGISTERED **PROFESSIONAL** LAND SURVEYOR

OREGON OCT. 17, 1975 BARBOUR BARRY B. 1051

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland

Doug Moser

October 21, 1980

Office of County Surveyor County State of County Surveyor State of County Surveyor I hereby certify that the vector of the County Cou	ithin instrument was filed in this office UNION COUNTY
(COUNTY OFFICIAL)	(DEPUTY) to Received
Form R6-7100-57 (9/71)	ੋ†= Fi ^l ed <u>ਦੇ ਫ਼ਸ਼ਰ—798-274</u>
	Ву
	Fi'e No. 394-84 R