
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by W. B. Barr under GLO Contract Number 388, dated May 7, 1881. Surveyor General record states: Set Basalt Rock 14x10x4 for corner.

A Pine 40 in. diameter bears N 35° W, 111 lks. dist. A Pine 18 in. diameter bears N 4½° E, 119 lks. dist. A Pine 24 in. diameter bears S 77° E, 40 lks. dist.: A Fir 24 in. diameter bears S 40° E, 90 lks. dist.



No record of subsequent monumentation found in Union County survey records

Description of corner evidence found:

Found no evidence of the original corner monument. Found A 26" Pine stump bears N $4\frac{1}{2}$ ° E, a distance of 119 lks, rotted scribes visible. Found A 24" P. Pine stump bears S 77 E, a distance of 40 lks, Rotted, scribes visible. Found A 29" P. Pine stump bears N 35° W, a distance of 52.5 feet, Rotted, scribes visible

Found a $1\frac{1}{4}$ " O.D. pipe bears N 4° E, 12. feet.

Description of monument and accessories I established to perpetuate the

original location of this corner: At record bearing and distance from the found bearing trees, is set a 2 1/2"x30" Aluminum pipe with aluminum cap marked as shown, 28 inches in the ground and raised a mound of stone with a 2 foot base for the corner position.

FROM WHICH:

A 15" P. Pine bears N 77° E, a distance of 66.80 feet, marked T4SR38E S8 BT

A 13" P. Pine bears S 40° E, a distance of 51.35 feet, marked T4SR38E S17 BT

A 15" P. Pine bears S 58° W. a distance of 20.39 feet, marked T4SR38E S 18 BT

A 14" P. Pine bears N 17° W, a distance of 77.95 feet, marked T4SR38E S 7 BT

I hereby certify that the above corner point was perpetuated as hereon described on August 6, 1990.

Witness: Jeff Petersen

T4S R38F POP S 7 | S 8 S 18 | S 17 1990 OPLS 991

PROFESSIONAL LAND SURVEYOR

O'R F.GON GREGORY T. BLACKMAN I used a steel tape and magnetic compass in the establishment of new accessories. I used 20° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 991 to the BT blaze.

State of, / hereb	County of	ffice
for record on the day of	SURVEYOR (DEPUTY	
Form R6-7100-57 (9/71)	Date Received 9 - / - 90	
	Date Filed 9-15-90 J-0	05

54-90R