## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner originally established by Henry M. Thatcher under GLO contract number 320 dated April 1, 1879. Surveyor General record states:


Set stone 24x18x2 for cor to secs 25,26,35 and 36 from which;

A black pine 15 in dia bears N710W 30 lks dist

A black pine 14 in dia bears N110E 43 lks dist

A black pine 16 in dia bears S 42°E 26 lks dist

A black pine 17 in dia bears \$290W 24 lks dist



No record of subsequent monumentation found in county records Description of corner evidence found:

Found a stone broken into 8 or 9 pieces with one groove visible

Found a 14" Lodgepole pine N110E 43 1ks down on face and rotting

Found a 16" Lodgepole pine S42°E 26 1ks dead down and rotting with scribes visible

Found a 17" Lodgepole pine S29°W 24 1ks dead down and rotting with scribes visible Found remains of Lodgepole pine N71°W 30 1ks rotted with hack mark visible only

The Northeast and Northwest BTs have both fallen on the corner stone which broke it into several pieces


Description of monument and accessories I established to perpetuate the original location of this corner: In place of stone, I set a 2½ x30" aluminum pipe with aluminum cap marked as shown, 28 inches in the ground from which:

A 16 inch diameter Spruce bears N53°E 38.01 feet marked T4S R41E S25 BT

A 8 inch diameter Lodgepole Pine bears \$77°E 33.73 feet marked T4S R41E \$36 BT

A 7 inch diameter Fir bears  $$53^{\circ}W$$  44.30 feet marked T4S R41E S35 BT A 9 inch diameter Fir bears N47°W 28.58 feet marked T4S R41E S26 BT

Buried the original stone South and alongside of monument Set steel fencepost approximately 5 feet North with 54-9 sign Corner monumented June 19, 1986 Witnesses: Greg Blackman and Rick Robinson



REGISTERED **PROFESSIONAL** AND SURVEYOR OREGON JULY 10, 1964 DUANE I. GRIFFITH

Brass washer marked OPLS 644 nailed to BT blaze. Used steel tape and magnetic compass with 20° East declination. Distances to the BTs are to a 50d spike set in right side of tree when facing tree, unless otherwise stated.

Office of County of	
State of, I hereby certify that the within	n instrument was filed in this office
for record on the day of , 19 , 19	
ICOUNTY OFFICIALUNION COUNTY SURVEYOR	(DEPUTY)
R6-7100-57 (9/71)	A., a a

Form F

U.S. GOVERNMENT PRINTING OFFICE - 1983-793-276