


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established in 1882, by Rufus S. Moore, under General Land Office Contract No. 451. Surveyor General's records state: Set a basalt stone 17" x 9" x 7" - 12" in ground for 1/4 sec. cor. marked 1/4 on North face, from which:  
A pine 6" dia. bears N 67 W, 8 lks. dist. marked 1/4 S BT.  
A pine 6" dia. bears S 82 E, 11 lks. dist. marked 1/4 S BT.



Description of corner evidence found:

At assumed corner location I found no acceptable evidence of stone as previously described, however I did find the remains and traces of the scribing 1/4 S BT on both bearing trees lying on the ground, and could determine the original location of both bearing trees.

Description of monument and accessories I established to perpetuate the original location of this corner:

As the evidence in the vicinity of the corner agrees with the GLO original record, at the location reconstructed from the position of the original bearing trees, I set a 2 1/2" brass cap on a 30" galv. iron pipe and being stamped as shown above in the ground, with a large mound of stone around the monument.

New bearing trees:

A doug fir 12" dia. bears N 86 W, 34.94 feet and acscribed 1/4 S S 8 BT.  
A doug fir 12" dia. bears N 58 E, 9.68 feet and scribed 1/4 S S 9 BT.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*James H. Hambleton*  
8-21-78

OREGON  
JULY 10, 1964  
JAMES H. HAMBLETON  
645

I hereby certify the above corner monument was re-established as herein described in August 1978.

Witnesses:

*Leonard E. Brown*  
Crew Chief

*L. D. Shibe*  
Instrument Man

Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....

(COUNTY OFFICIAL)

(DEPUTY)

<b>UNION COUNTY SURVEYOR</b>	
Date Received	_____
Date Filed	_____
By	_____
File No.	554-84R