History of original corner establishment:

Original survey by General Land Office contract survey The original notes state. Set a post from which;

A pine 5 in diam bears S86°E 79 lks dist marked T5S R34E S15BT; A pine 8% in diam bears S10°W 127 1ks dist marked 75S R34E S16BT:

A pine?" in diam begrs N13°W 90 lks dist marked T5S R34E S9BT; A pine 5" in diam bears N39°E 59 lks dist marked T5S R3#E S10BT;

		7.	13	Mass
	HAGRA	N		
	T53	R34	EWM .	
	S9	ST	0	
,	SI	6 51	5	

Found - A pine 26" in diam bears N39°E 59 lks dist with scribe visible.

A pine snag 24" in diam bears Sl0°W 127 lks dist with scribe visible.

A pine snag 12" in diam bears N13°W 90 lks dist with scribe visible.

REGISTERED OREGON AND SURVEYOR MAY 4, 1956 JAMES G. VOELZ 381

ent and accessories I established to perpetuate the Description of monum

ariginal location of this corner

AT the position of the corner I set a 2" galvanized pipe 30" long with a bronze
cap on top and a 8" plate welded to bottom. The pipe set to a depth of 6" and reaised a stone monument.

I stamped the disk

	OR R34E
S9	310
316	315 IC 381
ORE L	rc 381

From the monument the original bearing trees are; A pine 26" in diam bears N39°E 59 lks dist.

I set the following new bearing trees;

A pine 14" in diam bears S45°E 114.8 ft. dist marked T5S R34E S15BT;

A pine 9" in diam bears S53°W 134.2 ft dist marked T5S R34E S16BT;

A pine 14" in diam bears N8.W 64.2 ft. dist marked T5S R34E S9BT;

(distance measured to center of respective trees and marked with scribe)
I set a steel fence post with USFS sign 54-4 attached. USFS bearing tree signs were placed on bearing trees facing the corner.

Office of County surveyor County of Union State of Oregon , I hereby certify that the within instrument w	UNION COUNTY
for record on the .9. day of Sept	
(COUNTY OFFICIAL)	Date Received
	Date Filed
	Ву
	563-84