


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

No previous history

m-20



Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 2 1/2" brass cap in a 30" galv. iron pipe, and stamped as shown above, in the ground, and placed a large mound of stone around the monument.

New bearing trees:

- A pine 18" dia. bears N 55 E, 75.0 feet scribed 1/16S S 14 BT.
- A pine 13" dia. bears S 61 E, 32.67 feet scribed 1/16S S 14 BT.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton
8-21-78

OREGON
JULY 10, 1964
JAMES H. HAMBLETON
645

I hereby certify the above corner monument was re-established as herein described in August 1978.

Witnesses:

Leonard E. Green
Crew Chief

L. O. Shuler
Instrument Man

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by

(COUNTY OFFICIAL)

(DEPUTY)

DEWITT COUNTY
SURVEYOR

Received _____

☆ GPO—798-276

Filed _____

By _____

File No. 586-84R