


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

m-21

History of original corner establishment:

No previous history



Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 2 1/2" brass cap in a 30" galv. iron pipe, and stamped as shown above, in the ground, and placed a large mound of stone around the monument.

New bearing trees:

A pine 1 1/4" dia. bears N 80 W, 37.0 feet scribed 1/16S S 14 BT.
A pine 9" dia. bears N 81 E, 17.25 feet scribed 1/16S S 13 BT.

REGISTERED PROFESSIONAL LAND SURVEYOR

James H. Hambleton
8-21-78

OREGON JULY 10, 1964 JAMES H. HAMBLETON 645
--

I hereby certify the above corner monument was re-established as herein described in August 1978.

Witnesses: *Leonard E. Green*
Crew Chief

L. D. Huber
Instrument Man

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR
Date Received _____
Date Filed <small>☆ GPO-798-276</small> _____
By _____
File No 587-84R