


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. R-23

History of original corner establishment:

The original subdivision of T4S, R34E was by Rufus S. Moore under Contract No. 451, approved Feb. 1, 1884. He set a post, from which a 14" Pine bears N27°E, 5 lks., and a 10" pine bears S27°E, 37 lks.



Description of corner evidence found:

No monument or evidence found.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2.5" aluminum cap on 2 3/8"x30" aluminum pipe rising 8" above ground. Cap is stamped: Corner set by proportion. Set steel fence post 2.3 ft. north.

T5S R34E
1/4 S24
S25
RLS 1844
1984

New BT's:

- A 6" L. Pine bears N42°E, 8.7 ft., blazed & scribed; 1/4 S24 BT.
- A 6" L. Pine bears S1 3/4°E, 6.2 ft., blazed & scribed; 1/4 S25 BT.

Brass LS 1844 disc in lower end of blaze. Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 3/4°E

Witness; Duane Scott

Corner is found in area of young lodgepole 1000 ft. north of Lookout Creek, 1600 ft. east of location poster on 8" tamarack west side Road 5160-205.

I hereby certify the above described corner monument and/or accessories was established as described on June 22, 1984.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David E. Scott

OREGON
JULY 13, 1979
DAVID E. SCOTT
1844

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY
SURVEYOR

Date Received 10-17-84
 Date Filed 10-24-84
 By G. LANGLITZ DEPUTY
 File No. 963-84 R