

R623

Form 9600-9  
(December 1979)  
(Formerly 9100-9)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

23

FIELD NOTES  
OF THE

REPOINTMENT OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 38 EAST,

[Lined area for field notes]

Of the WILLAMETTE Meridian,  
in the State of OREGON

EXECUTED BY

Scott R. McIntyre, Cadastral Surveyor

[Lined area for signature]

Under special instructions dated July 13, 19 79, approved July 17, 1979

which provided for the surveys included under U.S. Survey/Group  
Number 1000, and assignment instructions dated July 30, 19 82

Survey commenced AUGUST 20, 19 82  
Survey completed AUGUST 31, 19 82

UNION COUNTY  
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ, DEPUTY

File No. 806-84 R

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAINS

A fir, 7 ins. diam., bears N. 46° W., 18½ lks.  
dist., mkd. T58 R37E S12 BT.

Set a steel fence post alongside aluminum post.

The ¼ sec. cor. of secs. 7 and 12, on the W. bdy. of the  
Tp., determined at record bearing and distance from the  
remaining original bearing tree:

A fir, 15 ins. diam., bears N. 15° E., 14 lks.  
dist., with scribe mark S visible on partially  
opened blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 22  
ins. in the ground, in a collar of stone, with aluminum  
cap mkd.

T 5 S  
R 37 E R 38 E  
¼  
S 12 | S 7  
1982

from which a new bearing tree

A spruce, 25 ins. diam., bears S. 37° W., 55 lks.  
dist., mkd. ¼ S12 BT.

Corner is located on E. bank of dry creek bed, course S.

Subdivisions, T. 5 S., R. 38 E.,  
Willamette Meridian, Oregon

(Remonumenting corners established by William B. Barr,  
U. S. Deputy Surveyor, in 1881)

The cor. of secs. 11, 12, 13, and 14, determined from the  
remains of the original bearing trees:

A root hole, bears N. 38° E., 32 lks. dist., with  
a down pine alongside, 10 ins. diam., with  
illegible scribe marks visible on opened and  
decayed blaze. (Record, N. 47° E.)

A decayed pine stump, 20 ins. diam., bears S. 48° E.,  
60 lks. dist., with scribe marks S BT visible on  
weathered and open blaze.

A decayed larch stump, 12 ins. diam., bears  
S. 51° W., 86 lks. dist., no marks visible.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

T 5 S R 38 E  
S 11 | S 12  
S 14 | S 13  
1982

UNION COUNTY  
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ, DEPUTY

File No. 806-84 R

PAGE 2/2