

N-7

R623

Form 9600-9
(December 1979)
(formerly 9188-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

23

FIELD NOTES

OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 38 EAST,

[Blank lined area for field notes]

Of the WILLAMETTE Meridian,

In the State of OREGON

EXECUTED BY

Scott R. McIntyre, Cadastral Surveyor

Under special instructions dated July 13, 19 79, approved July 17, 1979

which provided for the surveys included under U.S. Survey/Group
Number 1000, and assignment instructions dated July 30, 19 82

Survey commenced August 20, 19 82
Survey completed August 31, 19 82

UNION COUNTY SURVEYOR	
Date Received	<u>2-2-84</u>
Date Filed	<u>2-28-84</u>
By	<u>G. LANGLITZ, DEPUTY</u>
File No.	<u>830-84 R</u>
Page <u>1/3</u>	

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CROSS

from which a new bearing tree

A ponderosa pine, 13 ins. diam., bears N. 84½° W.,
69½ lks. dist., mkd. ¼ S19 BT.

Deposit corner stone and set a steel fence post
alongside aluminum post.

The cor. of secs. 17, 18, 19, and 20, determined at record
bearing and distance from which the remains of the orig-
inal bearing trees:

A root hole, bears N. 50° E., 68 lks. dist., with
a down pine alongside, 24 ins. diam., with scribe
marks T58 R38E S17 BT visible on open blaze.

A root hole, bears S. 64° E., 50 lks. dist., with
a down and decayed pine alongside, size indeter-
minate, no marks visible.

A root hole, bears N. 47° W., 43 lks. dist.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 15
ins. in the ground, to solid rock, in a mound of stone,
¾ ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E
S 18 | S 17
S 19 | S 20
1982

from which new bearing trees

A fir, 11 ins. diam., bears N. 69° E., 78 lks.
dist., mkd. T58 R38E S17 BT.

A fir, 20 ins. diam., bears S. 82° E., 43½ lks.
dist., mkd. T58 R38E S20 BT.

A fir, 25 ins. diam., bears S. 69° W., 99 lks.
dist., mkd. T58 R38E S19 BT.

A fir, 20 ins. diam., bears N. 64° W., 50 lks.
dist., mkd. T58 R38E S18 BT.

Set a steel fence post alongside aluminum post.

Corner is located 50 lks. N. of abandoned dirt road, 15
lks. wide, bears N. 75° W. and S. 75° E.

The ¼ sec. cor. of secs. 17 and 20, determined at record
bearing and distance from the original bearing trees:

A ponderosa pine, 18 ins. diam., bears S. 74° W.,
81 lks. dist., with scribe marks 4 S visible on
opened blaze.

A ponderosa pine, 48 ins. diam., bears N. 20° W.,
55 lks. dist., with opened blaze, no marks
visible.

At the corner point

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGRISH, DEPUTY

File No. 830-84R

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

UNION COUNTY
SURVEYOR

Order Resolved 2-2-84

Order Filed 2-28-84

G. LANGLITZ

Order No. 830-84R

Set a file, 12 ins. long, 6 ins. below surface of dirt road, 15 lks. wide, bears E. and W.

from which a reference monument

An aluminum post, 28 ins. long, 2½ ins. diam., set 12 ins. in the ground, to solid rock, in a mound of stone, 4 ft. base, to top, for a reference monument, bears North, 38 lks. dist., with aluminum cap mkd. T58 R38E ¼ S17 25 FT TO COR RM 1982 and an arrow pointing to the corner.

Set a steel fence post alongside aluminum post.

The cor. of secs. 7, 8, 17, and 18, determined at record bearing and distance from the remains of the original bearing trees:

A decayed pine stump, size indeterminate, bears N. 86° E., 13 lks. dist., no marks visible.

A pine snag, 10 ins. diam., bears S. 63° E., 8 lks. dist., with scribe marks S17 BT visible on open blaze.

A larch, 15 ins. diam., bears S. 63° W., 20 lks. dist., with healed blaze.

A pine snag, 10 ins. diam., bears N. 34° W., 52 lks. dist., with scribe marks S7 BT visible on open blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with aluminum cap mkd.

T 5 S R 38 E
S 7 S 8
S 18 S 17
1982

from which new bearing trees

A spruce, 29 ins. diam., bears N. 22° E., 56 lks. dist., mkd. T58 R38E S8 BT.

A fir, 10 ins. diam., bears S. 70° E., 44 lks. dist., mkd. T58 R38E S17 BT.

A spruce, 6 ins. diam., bears N. 53° W., 25½ lks. dist., mkd. T58 R38E S7 BT.

Set a steel fence post alongside aluminum post.

Corner is located 45 lks. N. of dry creek bed, course E.

The ¼ sec. cor. of secs. 8 and 17, determined at the center of a root hole, with the remains of the original corner tree alongside, a fir, 14 ins. diam., with scribe mark S visible on opened blaze, from which the remains of the original bearing trees:

A spruce, 28 ins. diam., bears S. 43° W., 20 lks. dist., with healed blaze.

CHAINS

At
Set
ins
cap

fr

Cor
cor

Th
be
be

At
Se
in

fr

PAGE 3/3