

V-13

R623

Form 9600-9
(December 1979)
(formerly 9100-9)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

23

FIELD NOTES
OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 38 EAST,

[Lined area for field notes]

Of the WILLAMETTE Meridian,
in the State of OREGON

EXECUTED BY

Scott R. McIntyre, Cadastral Surveyor

Under special instructions dated July 13, 19 79, approved July 17, 1979

which provided for the surveys included under U.S. Survey/Group
Number 1000, and assignment instructions dated July 30, 19 82

Survey commenced August 20, 19 82

Survey completed August 31, 19 82

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ, DEPUTY

File No. 810-84 R

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAINS

Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E

S 10 | S 11
1982

from which a new bearing tree

A fir, 11 ins. diam., bears N. 75° W., 71 lks. dist., mkd. ¼ S10 BT.

Deposit corner stone alongside aluminum post.

The cor. of secs. 27, 28, 33, and 34, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears N. 47° E., 48 lks. dist., with a down and decayed pine alongside, 36 ins. diam., with scribe marks T58 R38E S27 BT visible on open blaze.

A ponderosa pine, 20 ins. diam., bears S. 25° E., 40 lks. dist., with scribe marks 34 visible on partially healed blaze.

A sawed pine stump, 20 ins. diam., bears N. 31° W., 26 lks. dist., no marks visible.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam, 20 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E

S 28 | S 27
S 33 | S 34
1982

from which new bearing trees

A fir, 10 ins. diam., bears N. 16° E., 52½ lks. dist., mkd. T58 R38E S27 BT.

A fir, 12 ins. diam., bears S. 87° W., 26 lks. dist., mkd. T58 R38E S33 BT.

A fir, 5 ins. diam., bears N. 41° W., 47½ lks. dist., mkd. T58 R38E S28 BT.

Set a steel fence post alongside aluminum post.

The cor. of secs. 21, 22, 27, and 28, determined at record distance from the remains of the original bearing trees:

A sawed pine stump, 22 ins. diam., bears N. 24° E., 62 lks. dist., with scribe marks T58 R38E visible on open blaze.

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGUTZ, DEPUTY

File No. 810-84R

PAGE 2/2