


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

No previous history.



Description of corner evidence found:

No evidence found.

Description of monument and accessories established to perpetuate the original location of this corner:

I established the position of this 1/16 corner by survey. I then set an Alum. cap on a 2" x 30" pipe, with a magnet fixed in the cap, at the corner location. I buried the pipe to within 6" above the surface of the ground. I then placed a mound of stone 3 feet dia. and 1 foot high covering the monument. From which I set two bearing trees:

A pine 7" dia. bears S 69 21 W, 47.80 feet and scribed 1/16S S 13 BT.  
 A pine 13" dia. bears S 29 47 E, 31.70 feet and scribed 1/16S S 18 BT.

|                              |                            |
|------------------------------|----------------------------|
| <b>UNION COUNTY SURVEYOR</b> |                            |
| Date Received                | <u>9-22-87</u>             |
| Date Filed                   | <u>9-25-87</u>             |
| By                           | <u>G. LANGRISH, Deputy</u> |
| File No.                     | <u>125-87 R</u>            |

|  |
|--|
| REGISTERED PROFESSIONAL LAND SURVEYOR                |
| <i>James H. Hambleton</i>                            |
| <u>9-25-87</u>                                       |
| OREGON<br>JULY 10, 1964<br>JAMES H. HAMBLETON<br>645 |

REFER TO SURVEY 28-87

Office of..... County of.....  
 State of....., I hereby certify that the within instrument was filed in this office  
 for record on the..... day of....., 19.....  
 ..... by .....  
 (COUNTY OFFICIAL) (DEPUTY)