


V-17 T5S R41E

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

2 $\frac{1}{2}$ " IRON Post 28" Long set 22" in Ground
with 5' Steel Fence post Along side



ACCESSORIES DESCRIBE NEW BT's WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

A Fir 10" BRS N44 $\frac{1}{2}$ E 26 LKS MKD T5S R41E S26 BT
A Fir 10" BRS S21 \circ E 57 LKS MKD T5S R41E S35 BT
A Fir, 8" BRS S56 \circ W 57 LKS MKD T5S R41E S34 BT
A Pine 9" BRS N66 \circ W 60 LKS MKD T5S R41E S27 BT

Work Done By SALBRIGHT Title CADA STY A1 Date 9/24/71 State Registration No. R15822 R141
Certified Cor. Record Prepared? Yes No Filed At: _____ Date _____

REMARKS

Index File No. T. R. M. Tract or Surv. No. Cor. 12
13

UNION COUNTY SURVEYOR

Date Received _____

Date Filed 12-28-87

By G. LANGSTROM, DEPUTY

File No. 437-87R

L1-1

T. 5 S., R. 41 E., Willamette Meridian, Oregon

	CHAINS	<p>The following field notes describe the remonumentation of certain original corner points, township 5 south, range 41 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed".</p> <p>The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.</p> <p>The mean magnetic declination is 20° E.</p>
		Subdivision, T. 5 S., R. 41 E., Willamette Meridian, Oregon
		(Remonumenting corners established by Henry M. Thatcher, Deputy Surveyor, in 1879)

The cor. of secs. 26, 27, 34, and 35, determined at record distance from the original bearing trees:

A western larch, 20 ins. diam., bears N. 17° E., 91 lks. dist., no marks visible on open blaze.

A decayed fir stump, size indeterminate, bears S. 2° E., 133 lks. dist., with scribe marks BT visible on open blaze. (Record, S. 5° E.)

A root hole, bears S. 66° W., 111 lks. dist., with a down fir alongside, size indeterminate, with scribe marks S34 BT visible on open blaze.
(Record, S. 65° W.)

A decayed fir stump, size indeterminate, bears N. 42° W., 124 lks. dist., with fragmentary scribe marks visible on open blaze. (Record, N. 47° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 5 S R 41 E			
S 27	S 26		
S 34	S 35		
1971			

from which new bearing trees

A fir, 10 ins. diam., bears N. 44½° E., 26 lks. dist., mkd. T5S R41E S26 BT.

A fir, 10 ins. diam., bears S. 21° E., 57 lks. dist., mkd. T5S R41E S35 BT.

A fir, 8 ins. diam., bears S. 56° W., 57 lks. dist., mkd. T5S R41E S34 BT.

A ponderosa pine, 9 ins. diam., bears N. 66° W., 60 lks. dist., mkd. T5S R41E S27 BT.

Set 5 ft. steel fence post alongside iron post.

UNION COUNTY
SURVEYORDate Received 3/5/13Date Filed 3/5/13By NLGFile No. 017-2013R

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon**

CHAINS	
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
35.50	Oil surfaced road, 25 lks. wide, bears NW. and SE.
40.640	The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.
	$\begin{array}{c} \text{T } 5 \text{ S } \text{ R } 41 \text{ E } \\ \text{S } 27 \quad \quad \text{S } 26 \\ \hline \text{S } 34 \quad \quad \text{S } 35 \\ 1971 \end{array}$
	from which the remains of the original bearing trees
	A larch, 22 ins. diam., bears N. 14° E., 91 lks. dist., with healed blaze. (Record, N. 17° E.)
	A root hole, bears S. 5° E., 133 lks. dist., with uprooted pine log alongside, 26 ins. diam., no marks. (Record, S. 2° E.)
	A root hole, bears S. 65° W., 111 lks. dist., with fragmentary scribe marks visible on detached blaze, loose alongside. (Record, S. 66° W.)
	A broken pine stump, size indeterminate, bears N. 47° W., 124 lks. dist., no marks. (Record, N. 42° W.)
	and the remains of bearing trees mkd. by Albright
	A fir snag, 15 ins. diam., bears N. $41\frac{1}{2}^\circ$ E., 26 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, N. $44\frac{1}{2}^\circ$ E.)
	A fir, 17 ins. diam., bears S. 23° E., 57 lks. dist., with healed blaze. (Record, S. 21° E.)
	A fir snag, 10 ins. diam., bears S. $53\frac{3}{4}^\circ$ W., 57 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, S. 56° W.)
	A pine stump, 10 ins. diam., bears N. 69° W., 60 lks. dist., with scribe marks T5S R41E S27 BT on pine log alongside. (Record, N. 66° W.)
	and new bearing trees
	A ponderosa pine, 25 ins. diam., bears N. 65° E., 23 lks. dist., mkd. T5S R41E S26 BT.
	A larch, 14 ins. diam., bears S. 22° W., 60 lks. dist., mkd. T5S R41E S34 BT.
	A ponderosa pine, 17 ins. diam., bears N. $45\frac{1}{2}^\circ$ W., 20 lks. dist., mkd. T5S R41E S27 BT.
	A steel fence post is set alongside the stainless steel post.

UNION COUNTY
SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By M. L. Golen

File No. 144-2013R