

47
T5S 42 N03

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 42 E., Willamette Meridian, Oregon

CHAINS

Set 5 ft. steel fence post alongside iron post.

The cor. of secs. 17, 18, 19, and 20, determined at record distance from the remaining original bearing trees:

A western larch, 18 ins. diam., bears N. 35° E., 37 lks. dist., with scribe marks S R42E S7 visible on opened blaze. (Record, N. 40° E.)

A lodgepole pine, 13 ins. diam., bears S. 50½° W., 78 lks. dist., with fragmentary scribe marks visible on open blaze. (Record, S. 45° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 42 E
S 18 S 17
S 19 S 20
1971

from which new bearing trees

A lodgepole pine, 9 ins. diam., bears N. 36° E., 53 lks. dist., mkd. T5S R42E S17 BT.

A white fir, 8 ins. diam., bears S. 34° E., 104 lks. dist., mkd. T5S R42E S20 BT.

A lodgepole pine, 11 ins. diam., bears S. 27½° W., 7½ lks. dist., mkd. T5S R42E S19 BT.

A lodgepole pine, 9 ins. diam., bears N. 64½° W., 61 lks. dist., mkd. T5S R42E S18 BT.

Set 5 ft. steel fence post alongside iron post.

The ¼ sec. cor. of secs. 18 and 19, monumented with the original basalt stone, 16 x 12 x 6 ins., firmly set, 14 ins. in the ground, marked ¼ on N. face, from which the only remaining original bearing tree:

A fir, 22 ins. diam., bears S. 20° E., 12 lks. dist., with scribe marks ¼ S19 visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 42 E
¼ S 18
S 19
1971

from which new bearing trees

A lodgepole pine, 9 ins. diam., bears N. 59¾° E., 55 lks. dist., mkd. ¼ S18 BT.

UNION COUNTY SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 391-2013R