


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Z-1, 5-43  
Z-25, 5-42

**History of original corner establishment:**

W. B. Barr conducted the survey of the exterior line of Township 6 South, Range 42 East, W.M., May 29 to June 26, 1882, under GLO Contract No. 443, dated May 29, 1882.

For the corner point Barr set a volcanic rock 24 ins. x 10 ins. x 10 ins. in the ground, marked SC and 6 notches on the North, East and West sides. from which:



- A Fir, 15 ins. diam., bears N. 66° E., 125 lks. dist., mkd T5E R43E S31 BT.
- A Fir, 10 ins. diam., bears N. 31° W., 140 lks. dist., mkd. T5S R42E S36 BT.
- A Fir, Balsam, 8 ins. diam., bears S. 80° W., 34 lks. dist., mkd. T6S R43E S6 BT.

**Description of corner evidence found:**

Found a live 30 ins. diam. Douglas fir, bearing N. 66° E., 82.5 ft., dist., mkd. with a blaze has healed over and has been chopped into so a partial scribe is visible, reading 3E 31.

<b>UNION COUNTY SURVEYOR</b>
Date Received <u>5-1-89</u>
Date Filed <u>5-15-89</u>
By <u>G. LANGLITZ, DEPUTY</u>
File No. <u>104-89 R</u>

**Description of monument and accessories established to perpetuate the original location of this corner:**

Set a 2½ in. x 30 in alum. pipe with a 2½ in. alum. cap 24 ins into the ground. Constructed a 36 in. diam. stone mound around the monument. The cap is marked as shown in the corner diagram, Reestablished the corner point from the found bearing tree, using record bearing and distance.

From the corner point:

A 7 ins. diam. Alpine fir bears N. 79° W., 7.5 ft. dist., mkd. T5S R42E S36 BT.

Set a steel fence post 4 ft. South from the monument and attached a USFS 54-9 sign. Painted the face of the blaze and a 6 in. band around the bearing trees red. Attached I.D. washer and USFS 54-9 and 54-3 signs to bearing trees. Used a steel tape to measure to nail set in the side of the tree. Used 18½° declination on a staff compass for reading to the bearing tree. Brass ¾ in. diameter I.D. washer mkd. PLS 1206 is nailed to the new bearing tree between the B and T scribes.

This corner was monumented to USFS specifications on August 6, 1987, witnessed by Tom Fisk and Andy Marlette.

Office of.....County Surveyor..... County of...Union.....  
 Oregon  
 State of....., I hereby certify that the within instrument was filed in this office  
 for record on the..... day of....., 19.....  
 ..... by .....  
 (COUNTY OFFICIAL) (DEPUTY)

REGISTERED PROFESSIONAL LAND SURVEYOR
---

*James D. Hanley*

OREGON SEPTEMBER 23 1977 JAMES D. HANLEY 1206
--

Z-25