


RECOVERY NOTES

PROPERTY CORNER INVESTIGATION

N-3

LOCATION



T. 65 R. 42E
 Mer. Wm State Oregon
 Forest W-W Dist. Union

LEGEND

- Corner searched-no evidence
- Corner or accessory found
- Corner marked by perm. mon.

DESCRIPTION OF FOUND CORNER

MATERIAL: Basalt Rock SIZE: 20x18x8
 HEIGHT ABOVE GROUND: _____ CONDITION: Good
 MARKINGS: 1/4 on North mound of Earth

DESCRIPTION OF FOUND ACCESSORIES

No original accessories

NOTE: Indicate full investigative details on back of form.

PHOTO IDENTIFICATION

Symbol & date ENW 7/64 Line or Roll 8 Exposure 225
 How Identified Pin Point Where filed Union R.D.

RECOVERED BY: J. Demester

DATE: 9/1/66 TITLE: Forester

Form R6-5680-180 (4/61)

177
 7100-52 (3/68)
 5

HOW TO REACH CORNER
 DCL OR FAVIC
 3

2

USDA-FOREST SERVICE GPO 940-117
 Index File No. 13
 T. 65 R. 42E N.F. W-W
 R.D. Union County Union State ORE
 CORNER RECORD (SEARCH) (Ref. FSM 7151.4)
 Tract or Survey No. _____
 Cor. No. _____

UNION COUNTY SURVEYOR

Date Received _____
 Date Filed 12-23-87
 By G. LANGUITZ, Deputy
 File No. 403-87R


N-3

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

N-3

History of original corner establishment:

Corner was originally established by W.B. BARR, U.S. Deputy Surveyor, under Contract No. 443, dated May 29, 1882. Surveyor General records state: Set a basalt rock 20"X 18"X 8", set 15 inches in the ground and marked with a 1/4 on the North face.



See Survey 052-1994
Description of corner evidence found:

Found a stone 20"X 14"X 6", set in a small mound of stone with 1/4 chiseled on the North face. There is evidence of an old E.W. fence and a N.S. fence at this location.

Description of monument and accessories | established to perpetuate the original location of this corner:

At postion of the found stone:

Set a 2 1/2" X 30" aluminum pipe with a 2 1/2" aluminum cap, 26" in ground and surrounded with a mound of earth and stone. Deposited stone in hole along side of monument.
Attached sign 54-9 & 54-2 to steel fence post, set 3.6 feet North of monument.

New bearing objects established:

- A 5/8" X 30" rebar bears N 73°E - 19.6 feet, with a 1 1/2" aluminum cap stamped "RM 1/4 S18-19.6 FT 1106".
- A 5/8" X 30" rebar bears N 33°W - 19.6 feet, with a 1 1/2" aluminum cap stamped "RM 1/4 S18-19.6 FT 1106".
- A 5/8" X 30" rebar bears S 55 1/2°W- 22.6 feet, with a 1 1/2" aluminum cap stamped "RM 1/4 S19-22.6 FT 1106".
- A 5/8" X 30" rebar bears S 27°E - 23.9 feet, with a 1 1/2" aluminum cap stamped "RM 1/4 S19-23.9 FT 1106".

I hereby certify that the above corner monument was properly monumented to U.S.F.S standards by me on December 14, 1993.

Compass declination 18° East.

REGISTERED PROFESSIONAL LAND SURVEYOR

Will R. Wells

OREGON JULY 22, 1977 WILLIAM R. WELLS 1106

renews 12-31-94

Office of..... County of.....
 State of..... I hereby certify that the within instrument was filed in this office
 for record on the..... day of.....
 (COUNTY OFFICIAL) UNION COUNTY SURVEYOR (DEPUTY)

Form R6-7100-57 (9/71)

Date Received <i>11/3/94</i>
Date Filed <i>11/14/94</i>
By <i>Guyon To Blaker</i>
File No <i>154-1994 R</i>