


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

N-91

**History of original corner establishment:**

89.75 Set pine stake 4 ft. long, 4 ins. in diam. 24 ins. in the ground for 1/4 sec. corner marked 1/4 S on the North face, from which:

- A pine, 12 ins. diam., bears S.75°E., 16 lks. dist. mkd. 1/4 S BT.
- A tamarack, 5 ins. diam., bears N.32°W., 31 lks. dist. mkd. 1/4 S BT.



**Description of corner evidence found:**

**Description of monument and accessories I established to perpetuate the original location of this corner:**

No evidence of original monument or accessories found. Set a 3" diam. U.S.F.S aluminum capped pipe, 30" long, with magnet, at proportional position, 24" in ground with mound of stone to cap, from which:

- A fir, 18" diam., bears N.41°00'E., 40.64', scribed "1/4 S16 BT".
- A tamarack, 12" diam., bears N.70°00'E., 44.38', scribed "1/4 S16 BT".
- A fir, 16" diam., bears S.48°15'E., 68.58', scribed "1/4 S21 BT".
- A fir, 12" diam., bears S.58°45'W., 9.60', scribed "1/4 S21 BT".

**UNION COUNTY SURVEYOR**

Date Received 8/18/94

Date Filed 10/23/94

By [Signature]

File No. 042-1994R

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

[Signature]

OREGON  
JULY 15 1983  
RONALD E. STOLL  
2058

Office of \_\_\_\_\_ County of \_\_\_\_\_  
 State of \_\_\_\_\_ I hereby certify that the within instrument was filed in this office  
 for record on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_  
 \_\_\_\_\_ by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)

Y

N-91