

CORNER RECORD (SEARCH)  
(Ref. FSM 7151.4)

Tract or Survey No. \_\_\_\_\_

Cor. No. \_\_\_\_\_

Index File No. P 5

LS R. 42 E

R.D. UNION

County UNION

Sec. WM

N.F. WW

State ORE

CORNER DIAGRAM

19 ⊗ 20

DESCRIBE CORNER MONUMENT FOUND

STONE mound

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

32" PP IN SEC. 19 WITH SCRIB  $\frac{1}{4}$   
28" PP IN SEC. 20 SCRIBING S

PHOTO IDENTIFICATION DATA

Photo No. END-21-99

Filed At. \_\_\_\_\_

Object Ident. \_\_\_\_\_

Ident. By \_\_\_\_\_

Signature

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

I PUT F.S. LOCATION POSTER ON S<sup>W</sup> COR. 500' EAST OF  $\frac{1}{4}$  COR. ON UPPER SIDE OF ROAD

PLANE COORDINATE POSITION DATA

State \_\_\_\_\_ Zone \_\_\_\_\_

X \_\_\_\_\_

Y \_\_\_\_\_

Estab. By \_\_\_\_\_

Agency

Signature  
E.A.H.

Title \_\_\_\_\_

Division \_\_\_\_\_

Headquarters \_\_\_\_\_

Date

9/21/77

7100-52 (3/68)

UNION COUNTY SURVEYOR

Date Received \_\_\_\_\_

Date Filed 12-23-87

By G. LANGLITZ, DEPUTY

File No. 410-87R


P-5

# CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**History of original corner establishment:**

40.00 Set basalt rock 14 x 10 x 5 ins., 10 ins. in the ground, for  $\frac{1}{4}$  sec. corner marked  $\frac{1}{4}$  on the West side, from which:

- A pine, 26 ins. diam., bears N.25°W., 23 lks. dist. mkd.  $\frac{1}{4}$  S BT.
- A pine, 22 ins. diam., bears N.48°E., 32 lks. dist. mkd.  $\frac{1}{4}$  S BT.



**Description of corner evidence found:**

A pine stump, 42" diam., bears N.28°23'W., 14.89', blaze and scribe are visible.  
 A dead and down pine, 24" diam., bears N.47°27'E., 21.68', blaze and faint scribing visible.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

No evidence of original monument found. Set monument from found bearing trees Set a 3" diam. U.S.F.S aluminum capped pipe, 30" long, with magnet, 26" in ground with mound of stone to cap, from which:

- A fir, 12" diam., bears N.71°34'E., 41.56', scribed "T6S R42E S20 BT".
- A fir, 12" diam., bears S.23°21'E., 18.76', scribed "T6S R42E S20 BT".
- A fir, 12" diam., bears S.50°13'W., 37.67', scribed "T6S R42E S19 BT".
- A fir, 10" diam., bears N.50°07'W., 68.80', scribed "T6S R42E S19 BT".

**UNION COUNTY SURVEYOR**

---

Date Received 8/14/94

Date Filed 10/23/94

By *Allyn T. Blaker*

File No. 059-1994K



Office of \_\_\_\_\_ County of \_\_\_\_\_  
 State of \_\_\_\_\_ I hereby certify that the within instrument was filed in this office  
 for record on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_  
 \_\_\_\_\_ by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)

H

*P-5*