

5 | 4  
8 | 9

(S89°11'22"W) (2634.86)  
S 89° 06' 07" W 2635.27

4 3  
9 10

USED RECORD BEARING AND  
DISTANCE ON SURVEY 55-76  
N 00° 03' 25" W  
N 00° 08' 15" W

1324 86

8 9  
17 16

1331.18

(N 89° 24' 55" E)  
N 89° 20' 07" E

(5308.29)  
5307.95

2645.59

2663.68

2653.25

1326.62

2653.04

1328.40

5309.83  
(5310.25)

N 89° 24' 39" E

FND. 5/8" PIN  
10.5' NORTH  
13.25' WEST  
AT FENCE COR

FENCE COR  
2' N  
13' W

2659.16

1329.59

339.57

990.00

N 00° 00' 04" W  
(N 00° 05' 07" W)

N 00° 04' 10" W

1326.63

N 89° 29' 10" E

522.00

N 00° 00' 04" W

FND. 1/2" PIN  
12.8' WEST  
9.0' SOUTH  
AT FENCE CORNER

FENCE COR  
4' N  
19' W

804.50

804.50

522.00

468.00

990.00

N 89° 29' 10" E  
(N 89° 34' E)

5311.96  
(5312.32)

2655.98

2663.68

5327.36  
(5327.45)

N 00° 13' 35" W  
(N 00° 08' 45" W)

9 10

16 15

BASIS OF BEARING

SURVEY NUMBER 2-77

BEARING SWITCH TO SURVEY 55-76  
IS CLOCKWISE 00° 04' 50"

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

OREGON  
JULY 10, 1964  
DUANE I. GRIFFITH  
644

NO CONCRETE MONUMENT FOUND  
CORNER ESTABLISHED FROM  
REFERENCE POINTS

REFERENCE MATERIAL

- SURVEY NUMBERS:
- 28 - 70
  - 66 - 72
  - 68 - 72
  - 79 - 73
  - 111 - 73
  - 55 - 76
  - 2 - 77

DEED MF45097

LEGEND

- FOUND MONUMENT OF RECORD
- SET 5/8" x 30" IRON PIN WITH PLASTIC CAP MARKED B·G·A SURVEY MARKER
- ( ) RECORD BEARING AND DISTANCE

**BAGETT, GRIFFITH & ASSOCIATES**

La Grande, Oregon

Map of Survey

PARCELS IN SE 1/4 OF THE SW 1/4 OF SECTION 9

T 1 S, R 38 E W.M.

UNION COUNTY, OREGON

SURVEYED FOR	HUFF CONSTRUCTION CO.	
SURVEYED BY	d i g	8/77
Scale: 1" = 40'	Drawn by: S S Z	8/77

71-77