

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**


**HISTORY OF ORIGINAL CORNER ESTABLISHED:**

Not previously Established.

T 1 N R 38 E D-25

**DESCRIPTION OF CORNER EVIDENCE FOUND:**

None.



**DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO MONUMENT THE LOCATION OF THIS CORNER:**

At position determined by survey I set a 5/8" x 30" iron pin, 28" in the ground, with 2 1/2" aluminum cap marked as shown below, and in a 2' diam. mound of stone, from which:

**NEW BEARING OBJECTS:**


A 6" Ponderosa Pine bears North 50° East a dist. of 28.00 ft., marked S 1/16 S6 BT.  
A 14" Ponderosa Pine bears North 28° West a dist. of 15.20 ft., marked S 1/16 S1 BT.

Set fence post approx. 0.5 ft. North

I hereby certify that the corner was monumented on May 8, 2020.

Witness: Kyle A. Tucker

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR



OREGON  
June 2, 2010  
JEFFREY S. HSU  
83571

Renewal Date: June 30, 2021

GRIFFITH & BLACKMAN  
BAGGETT - T1N  
R38E R39E  
S 1/16  
S1 | S6  
OPLS 83571  
2020

**UNION COUNTY  
SURVEYOR**

Date Received 5/15/20  
Date Filed 5/15/20  
Filed By [Signature]  
File Number 033-2020R

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 14° East declination, the distances are to a 60d spike driven into the right side of the root crown of the bearing trees. A brass washer marked OPLS 83571 is attached to the BT blaze of the new bearing trees.