CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:
None

Survey 95-74 indicates "IP" at this corner position.

No record of subsequent monumentation found in UNION COUNTY survey records.



DESCRIPTION OF CORNER EVIDENCE FOUND:
None

See Survey Number 024-1997.

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:
At position determined by survey, I set a 2 1/2" x 30" aluminum pipe with 2 1/2" aluminum cap marked as shown below, 26" in the ground, with ring of stone.
BEARING TREES:
A 23" Ponderosa Pine bears S36°E, 51.0 feet, marked N1/16 S30 BT.

A 23" Ponderosa Pine bears S62°W, 96.5 feet, marked N1/16 S25 BT.

I hereby certify that the corner was monumented on August 1, 1997.
Witnesses: Jeff Madsen and Greg Blackman Jr.

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Jeffery P. Petersen
OREGON
JULY 20, 1993
JEFFERY P. PETERSEN
2625
Renewal Date: December 31, 1998



UNION COUNTY SURVEYOR

Date Received 8-6-97

Date Filed 8-6-97

Filed By R. Robinson Denney

File Number 012-1997 R

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 18° East declination, the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 2625 to the bearing tree blaze.

~~S-~~25

S-1