Dependent Resurvey of the West Boundary,
T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET	
2655.24	Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate dist., there is no remaining evidence of the original cor., not monumented.
	Descend over broken E. slope.
5310.48	Point for the cor. of secs. 19, 24, 25, and 30, at proportionate dist., there is no remaining evidence of the original cor., not monumented.
	N. 0° 01' 38" E., bet. secs. 19 and 24.
	Descend over broken NE. slope, through fir, tamarack, and pine timber.
2655.24	Point for the ¼ sec. cor. of secs. 19 and 24, at proportionate dist., there is no remaining evidence of the original cor., not monumented.
	Over broken slope.
5310.48	Point for the cor. of secs. 13, 18, 19, and 24, at proportionate dist., there is no remaining evidence of the original cor., not monumented.
	N. 0° 01' 38" E., bet. secs. 13 and 18.
	Ascend over broken Southerly slope, through fir, tamarack, and pine timber.
2655.24	Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate dist., there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. T 1 S R 37 E R 38 E 1/4 S 13 | S 18 2003
	from which
	A tamarack, 30 ins. diam., bears N. 89° E., 9.3 ft. dist., mkd. 1/4 S18 BT.

L-1

UNION COUNTY
SURVEYOR

Date Received 6/12/11

Date Filed 6/23/11

By R. Robinson, Deputy

File No. 026-2011R

Dependent Resurvey of the West Boundary,
T. 1 S., R. 38 E., Willamette Meridian, Oregon

FEET	
	A tamarack, 22 ins. diam., bears S. 18½° W., 23.3 ft. dist., mkd. 1/4 S13 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Across broken W. slope.
5310.48	Point for the cor. of secs. 7, 12, 13, and 18, at proportionate dist., there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 1 S R 37 E | R 38 E S 12 | S 7 S 13 | S 18 2003
	from which
	A spruce, 12 ins. diam., bears N. 56½° E., 26.9 ft. dist., mkd. T1S R38E S7 BT.
	A spruce, 25 ins. diam., bears S. 27° E., 61.2 ft. dist., mkd. T1S R38E S18 BT.
	A tamarack, 14 ins. diam., bears S. 73° W., 55.1 ft. dist., mkd. T1S R37E S13 BT.
	A tamarack, 18 ins. diam., bears N. 45¼° W., 62.7 ft. dist., mkd. T1S R37E S12 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Corner is located S. 30° W., 100 ft. dist. from a ravine, drains N. 50° W.
	N. 0° 01' 38" E., bet. secs. 7 and 12.
	Over broken slope, through fir, tamarack, and pine timber.
2655.24	Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate dist., there is no remaining evidence of the original cor., not monumented

L-1

UNION COUNTY
SURVEYOR

Date Received 6/12/11
Date Filed 6/23/11
By R. Robinson, Deputy
File No. 026-2011R