CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. ~~X~~ A-15 (T2S R40E

History of original corner establishment:

Corner was originally established by Henry Meldrum, under Contract No. 450, June 11, 1882. Surveyors General's notes state: "Set post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for 1/4 sec. cor., mkd. 1/4S on N. face; from which a tamarack, 18 ins. diam., bears S43°E., 64 lks. dist. mkd. 1/4S BT. A fir, 15 ins. diam., bears N46°E, 52 lks. dist. mkd. 1/4S BT."

DIAGRAM

T1SR40E
S34
1/4
S3
T2S

Description of corner evidence found:

Found no trace of record post. Found 30" white fir snag with open blaze and scribing. Measured S46°E, 34.3 ft. and found rotten stump bearing S43°E, 42.2 ft.

Description of monument and accessories I established to perpetuate the original location of this corner:

T1S R40E
S34
1/4
S3
T2S
OR PLS 1051
1980

At the above point set 2 1/2" X 30" galvanized pipe and brass cap marked: Set pipe 24" in the ground. No rock in the area.
From which by magnetic declination on N20°E:
A 16" white fir bears N52°E, 23.3 ft. scribed 1/4S34 BT.
A 9" white fir bears S69°E, 42.4 ft. scribed 1/4S3 BT.
Pa inted blazes red and 6" red band around. Placed 54-3s, 54-4s and brass washers stamped PLS 1051 on BTs. Placed 54-2 and 54-4 on steel fence post 5' east of the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Barry B Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Ray McVey
Daniel Rowland
Doug Moser
Ron Gilroy

November 19, 1980

Office of County Surveyor *County of* Union
State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 30th *day of* January, *19* 81
..... *by* .....
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received
Date Filed
By
File No. 3~~4~~0-84R

Form R6-7100-57 (9/71)