CERTIFIED RECORD OF LAND CORNER MONUMENTATION

A-11

History of original corner establishment:

Jacob C. Cooper
Contract No. 379
July 14, 1881
40.00 CH
Set a post 3½ ft. long, 3 ins. sq., 1½ ft. in the ground marked ¼s on North and South faces from which
A fir 12 in. dia. bears N 70° E, 39 Lks marked ¼s BT
A fir 4 in. dia. bears S 50° W, 15 Lks marked ¼s BT

DIAGRAM

T2N R38E
1/4 33/4
T1N R38E

Description of corner evidence found:

Fir 25" N 82° E, 25.70 ft., good condition, Blazes closed
(GLO Fir 12" N 70° E, 39 Lks.)

Fir 8" S 50° W, 15 Lks, Found dead and down with usable scribing.

Description of monument and accessories I established to perpetuate the original location of this corner

At the position described above, I set 2½" x 30" iron pipe 20" in the ground with a Brass Cap, marked as shown from which I scribe BT's.

Fir 14" S 22° W, 26.50 ft., scribed ¼s BT
Painted blazes and placed BT and Attn. sign and red band on above found BT.

I nailed a brass washer marked OPLS 1097 to BT blazes.
I set a steel fence post 5 ft. North with signs 54-4.
I painted a red band around BT's and face of scribe.
I used a steel tape and compass with 19° declination and measured a horizontal distance to the center of the BT's.
This corner was set 8/13/80, witness by Patrick Murphy.
See map of survey.

T 2N R38E
1/4 33/4
T1N R38E
1980
PLS 1097

REGISTERED PROFESSIONAL LAND SURVEYOR
James H Buisman
OREGON
JULY 22, 1977
JAMES H. BUISMAN
1097

Office of ..... *County of* .....
State of ..... *, I hereby certify that the within instrument was filed in this office for record on the* ..... *day of* .....
..... *by* .....
(COUNTY OFFICIAL) (DEPUTY)

...ION COUNTY SURVEYOR
Received
Date Filed
By
GPO 796-333
File No. 7-84 R

Form R6-7100-57 (9/71)