


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**HISTORY OF ORIGINAL CORNER ESTABLISHED:**

Corner originally established by Rufus S. Moore under GLO joint contract number 382 dated March 23rd, 1881. Surveyor General field notes state:

- Set Post for cor. to secs 1 & 12 from which:
- A pine 12 ins. diam. bears N58°E 88 lks. dist.
- A pine 16 ins. diam. bears N53°W 81 lks. dist.
- A pine 10 ins. diam. bears S37°W 55 lks. dist.
- A pine 24 ins. diam. bears S19°E 63 lks. dist.

T 2 N R 40 E E-25



**DESCRIPTION OF CORNER EVIDENCE FOUND:**

- A 31" Ponderosa Pine bears South 37° West, a dist. of 36.30 feet, alive and vigorous with healed blaze.
- A 14" Ponderosa Pine stump, 4' tall, bears North 73° West, a dist. of 53.46 feet, dead and standing with BT scribes visible.
- A stump hole bears North 58° East, a dist. of 58.08 feet, with fragments of decayed woody debris.

**DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO MONUMENT THE ORIGINAL LOCATION OF THIS CORNER:**

At record distance and bearing I set a 2 1/2" x 30" aluminum pipe, 26" in the ground with 3" aluminum cap marked as shown below, from which:

**NEW BEARING OBJECTS:**

- A 12" Ponderosa Pine bears North 52° East a dist. of 62.65 ft., marked T2N R41E S6 BT.
- A 14" Ponderosa Pine bears South 71° East a dist. of 20.65 ft., marked T2N R41E S7 BT.
- A 13" Ponderosa Pine bears North 4° West a dist. of 36.75 ft., marked T2N R40E S1 BT.

Set steel fence post approx. 1 foot East.

Falls on East edge of opening on an East aspect.

I hereby certify that the corner was monumented on August 20, 2019.  
Witness: Kyle A. Tucker

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

OREGON  
June 2, 2010  
**JEFFREY S. HSU**  
83571

Renewal Date: June 30, 2021

GRIFFITH & BLACKMAN

T2N

R40E R41E

S1 S6

---

S12 S7

2019

OPLS 83571

BAGETT

**UNION COUNTY  
SURVEYOR**

Date Received 8/27/19

Date Filed 8/27/19

Filed By N. G. Albin

File Number 044-201972

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 13° East declination, the distances are to a 60d spike driven into the right side of the root crown of the bearing trees. A brass washer marked OPLS 83571 is attached to the BT blaze of the new bearing trees.