CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner originally established by Rufus S. Moore under GLO joint contract number 382 dated March 23rd, 1881. Surveyor General field notes state:

Set Post for 1/4 sec. cor. from which:

A pine 36 ins. diam. bears N70°E 12 lks. dist.

A pine 28 ins. diam. bears N53°W 153 lks. dist.

DESCRIPTION OF CORNER EVIDENCE FOUND:

A 41" Ponderosa Pine bears North 70° East, a dist. of 7.92 feet, alive and vigorous with faint "B" scribing visible on a partially burnt and healed blaze. BLM bearing tree tag states "8 ft. to corner, Nov. 1957".

A 31" Ponderosa Pine bears North 53° West, a dist. of 100.98 feet, alive and vigorous with faint "/4" scribes visible on a partially burnt and

healed blaze.

S

T2N R40 EL-25

13

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO MONUMENT THE ORIGINAL LOCATION OF THIS CORNER:

At record distance and bearing from the faces of the trees, I set a 2 $\frac{1}{2}$ " x 30" aluminum pipe, 24" in the ground with 3" aluminum cap marked as shown below, from which:

NEW BEARING OBJECTS:

A 5/8" x 30" iron pin bears South a dist. of 22.50 ft., with 1 ½" aluminum cap marked S RP. Falls approx. 2 ½ feet East of old power pole. A 5/8" x 30" iron pin bears South 68° West a dist. of 11.05 ft., with 1 ½" aluminum cap

marked SW RP. Falls in Railroad right of way fence line.

Set steel fence post approx. 1 foot South.

Falls North of railroad right of way fence approx. 9 feet.

I hereby certify that the corner was monumented on August 22nd, 2019.

Witness: Kyle A. Tucker

REGISTERED **PROFESSIONAL** LAND SURVEYOR

June 2, 2010 JEFFREY S. HSU 83571

OREGON

Renewal Date: June 30, 2021

GRIFFITH & T2N R40E R41E 1/4 S13 2019 **OPLS 83571**

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 13° East declination, the bearings and distances are to the center of the aluminum caps.

UNION COUNTY SURVEYOR File Number 648-7019 K