CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Alonzo Gesner under GLO contract No. 683 and dated June 7, 1898.

Surveyor General records state:

Set basalt stone 20 \times 8 \times 5 ins 15 ins in ground at the point of instrsection for the closing Cor to Secs 18 and 19 marked CC on the E side with 8 notches on the N and S sides from which:

N-1**DIAGRAM** T 2 S T 2 S S 18 S 24 - CC S 19 R 40 E R 41 E 1987 ORLS 1639

A tamarack 14 ins diam bears $N53^{O}E$, 49 lks dist marked T2SR41ES18CC BT. A tamarack 14 ins dism bears $S59^{O}E$, 55 lks dist marked T2SR41ES19CC BT.

Description of corner evidence found:

Found a stone 22 x 7 x 5"(record, 20 x 8 x 5") firmly set with 3 notches on S side and fragmentary chisle work on N and E sides from which:

A tamarack windblow 17" dia and root stub brs S63°E, 37.2'(record, S59°E, 55 lks) mkd T2SR41ES19CC BT on open face.

A rotten windblow and root stub bre M53°E 40 lks 32 mm root stub bre M53°E 40 lks

A rotten windblow and root stub brs N53°E, 49 lks as per record, no marks identified.

UMION COUNTY SURVEYOR Date Received 9-1-87

60 No. 101-87 R

Description of monument and accessories I established to perpetuate the original location of this corner:

At position of found stone ...

Set $2\frac{1}{2}$ " aluminum cap on 2" aluminum pipe 20" in ground & 10" projecting out of ground with surrounding rock mound & 6' fence post alongside with sign 54-9 attached. Cap marked as shown in corner diagram. Buried stone alongside.

New bearing trees established: A red fir 21" dia brs N10 $\frac{1}{2}$ °E, 38.7' dist mkd T2SR41ES18CC BT. A white fir 17" dia brs S57 $\frac{1}{2}$ °E, 30.2' dist mkd T2SR41ES19CC BT.

Each BT has a sign 54-3 and signs 54-4 or 54-9 attached below a 6 " band of red paint, and each new BT has a brass washer marked PLS 1639 nailed flush with BT blaze.

Compass declination 170 East.

I hereby certify that the above described corner monument was properly remonumented by me and witnessed by Jim DeMastus on August 13, 1987. pin DeMeratur

LAND SURVEYOR

REGISTERED **PROFESSIONAL**

> OREGON JULY 14, 1978 WILLIAM L. HANLEY 1639

Office of	County	Surveyor	County of	Union
State of	Oregon	, / hereby cert	ify that the within	instrument was filed in this office
for record on the day of , 19				
by				
(COUNTY OFFICIAL)			•	(DEPUTY)