CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by Herman D. Gradon under contract No. 517 dated

September 30, 1884.

Record States:


Set basalt stone 10x8x8 ins., 7 ins. in the ground for 1/4 sec. cor.

From Which:

A fir, 10 ins. diam., bears S. 40° W., 25 lks. dist. A fir, 6 ins. diam., bears N. 43° E., 56 lks. dist.

Subsequent survey:

None found



32



Description of evidence found:

None found. True corner position falls in very steep and rocky creek bottom unsuitable for monumentation. I set an off-line Witness Corner as defined in the 2009 Manual of Surveing Instructions.

Description of monument and accessories established to perpetuate the location of this corner.

At position determined by survey, I set a 2 ins. diam. aluminum cap, on a 5/8 ins. diam. x 30 ins long iron rod, marked as shown. From which:

A 5/8" x 30" long iron rod with yellow plastic cap marked "BROCKAMP LAND SURVEYING PLS 78556" bears N. 10° E., 6.9 ft. dist. A 5/8" x 30" long iron rod with yellow plastic cap marked "BROCKAMP LAND SURVEYING PLS 78556" bears S. 75° E., 8.0 ft. dist. A 5/8" x 30" long iron rod with yellow plastic cap marked "BROCKAMP LAND SURVEYING PLS 78556" bears S. 20° W., 7.1 ft. dist. A 5/8" x 30" long iron rod with yellow plastic cap marked "BROCKAMP LAND SURVEYING PLS 78556" bears N. 67° W., 6.9 ft. dist.

Witness corner witness distance to True corner position is S. 23° 49' 26" W., 159.26 ft. dist.

Witness corner position falls on very steep South slope.

Bearings are made with a hand compass, magnetic declination = 15°E.

I hereby certify that the above corner point was perpetuated as herein described on 6/17/2018.

Witnessed by: Matt Brockamp, LS Austin Brockamp

UNION COUNTY
SURVEYOR

Date Received 7/9/18

Date Filed 9/13/18

Filed By LLG LLG

File Number 056-70187

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGÓN MAY 20, 2015 MATTHEW R. BROCKAMP 78556

Registration expires 12/31/2019

