


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

(T3SR35E) A-25
Index File No. ~~7-25~~

History of original corner establishment:

In 1874, under GLO Contract No. 201, J. Hurlburt set post 5 ft. long 5 ins. square marked T2S S31 on NE., R36E S6 on SE, T3S S1 on SW and R35E S36 on NW Faces. A Fir 15 ins. diam. bears N78°E, 19 lks. dist., marked T2S R36E S31 BT. A Fir 24 ins. dia. bears N74°W 29 lks. dist., marked T2S, R35E S36 BT. A Fir 24 ins. dia. bears S30°W 20 lks. dist., marked T3S R35E S1 BT. A Pine 24" dia. bears S24°E, 36 lks. dist., marked T3S R36E S6 BT.




Description of corner evidence found:

Found 33" P.Pine alive with open upper blaze and visible scribing "R36 S6", lower blaze is healed over.
Found 12" dia. rotted Fir stump 5 ft. tall and leaning with visible scribing "T2S R36E S31" with chaining notch below and BT blaze has been burnt - no scribing visible.
Found rotted remains of stump at record bearings and distance for possible SW and NW BT's.

No evidence of original post.

Description of monument and accessories established to perpetuate the original location of this corner:

At record bearing and dist. (N24°W, 23.76 ft) from S.E. found BT. Set 2½"x30" galvanized pipe with brass cap stamped:



Did not use NE stump because of the lean and not being able to determine the exact original location. Set pipe 23" in ground. No stones for mound.

Bearing Trees:

Found stump in S31 T2S R36E, Bears N79°E 12.6 ft.

New BT's:


- A Doug. Fir 10" dia. bears N42½°E, 12.7 feet, scribed T2S R36E S31 BT.
- A Doug. Fir 11" dia. bears S58°W, 70.2 ft., scribed T3S R35E S1 BT.
- A Doug. Fir 8" dia. bears N51°W, 22.9 ft., scribed T2S R35E S36 BT.

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, Oct., 1979. Set metal post 5 ft. south of corner with 54-4 sign attached.

Corner falls on slight SE slope approx. 150 ft. north of old seldom used logging road 0.5 miles SE of Road 2145 where it turns north.

Compass Declination: 18½° E Witnesses: R. Orton

I hereby certify the above described corner monument and/or accessories was established as described on July 30, 1982.



Office of.....Surveyor..... County of.....Union.....
 State of.....Oregon..... I hereby certify that the within instrument was filed in this office
 for record on the 4 day of OCTOBER, 1982
Howard L. Perry..... by Gary L. Langlitz
 (COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received _____	
☆ GPO 799-509	
Date Filed _____	
By _____	
File No. <u>222-84R</u>	