CERTIFIED RECORD OF LAND CORNER MONUMENTATION

A-7

History of original corner establishment:

Original Survey by General Land Office;
(contract survey 1863)

The original notes read;
At 40.00 ch. set post from which;
A pine 8" in diam bears N55°W 72 lks dist.
A spruce 6" in diam bears S5°W 38 lks. dist.

DIAGRAM
T3S, R38EWM
S 32
T4S, S 5

Description of corner evidence found:

A slab from the pine bearing tree was found with he "BT" scribe visible. No other poitive evidence was found at the corner. Evidence of the old fences were found that are now almost completely rotted away.

Description of monument and accessories I established to perpetuate the original location of this corner

At the position of the corner I set a 30" galvanized pipe with a bronze cap on top and an eight inch plate welded to the bottoms. The pipe was set to a depth of approx. 20" and back filled with stone and tamped earth.

I stamped the disk. →

¼ cor.
T3S, R38E
S 32
T4S, S 5
ORE LIC 381
1971

From the monument the original bearing trees were -(none)
Two new bearing trees were established.
A douglas fir 12" in diam bears N9°W a dist. of 11.2 ft. scribed ¼S BT; A white fir 7" in diam bears S36°E a dist of 5.1 ft. scribed ¼S BT. The distance measured to center of the respective trees.

REGISTERED
OREGON
LAND SURVEYOR
James G. Voelz
MAY 4, 1956
JAMES G. VOELZ
381

Office of County Surveyor County of Union
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 12 day of July 1971, at 8 o'clock A.M. (Seal)
County Surveyor (COUNTY OFFICIAL) by James G. Voelz (DEPUTY)

UNION COUNTY SURVEYOR
Date Received
Date Filed
By
File No. 521-84R

46-1971

Form R6-7100-57 (9/66)